

# TALON SUPER SOFT STAINLESS PLUMBER'S PUTTY MT-SPEC

## PRODUCT DESCRIPTION

### PRODUCT

**TALON PLUMBER'S PUTTY Super Soft Stainless Plumber's Putty**

### TYPE

**TALON PLUMBER'S PUTTY** is a pliable non-hardening putty for sealing rims of faucets, sinks, strainers, etc. Never cracks, hardens, dries out or mildews. **TALON PLUMBER'S PUTTY** sticks to metal, plastic, fiberglass and wood, but not to your hands.

**TALON PLUMBER'S PUTTY** is flexible and stretchable, spreads easily, and can be molded into rings or shaped to the precise configuration needed. It provides a gas proof, fume proof, odor proof, insect proof and watertight seal.

### RECOMMENDED USES

Used for setting bowls, fixtures, faucets, basin cocks, strainers, plugs, sink frames as well as many other sealing and caulking jobs.

### PHYSICAL PROPERTIES

Specific Gravity: 1.97 ±0.2  
Solubility in water: Insoluble

### COLOR/CONSISTENCY

Off white / Heavy paste

### TEMPERATURE RANGE USE

-50°F (-45°C) to 140°F (60°C)

Application: 40°F (4°C) to 100°F (37°C)

### U.S. FEDERAL SPECIFICATION

Meets or exceeds Federal Specifications  
TT-P-1536A.

### ENVIRONMENTAL STATEMENT

**TALON PLUMBER'S PUTTY** is classified as non-hazardous as defined by OSHA 29 CFR 1910.1200

### MT-SPEC

© 2022 J.C. Whitlam Manufacturing Company  
This product is manufactured in the U.S.A.

## PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Plastic Tub	
MT1	14 oz. (.4 kg)
MT3	3 lbs. (1.4 kg)
MT5	5 lbs. (2.3 kg)
Plastic Pail w/ Handle	
MT15	15 lbs. (6.8 kg)

## SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
MT1	25 lbs. (11.3 kg)	24
MT3	19 lbs. (8.6 kg)	6
MT5	32 lbs. (14.5 kg)	6
MT15	67 lbs. (30.4 kg)	4

## WEIGHT PER U.S. GALLON

16.27 lb/gal (7.38 kg) ± 0.02

## DIRECTIONS FOR USE

1. Take out required amount and form the putty to the approximate shape needed. **TALON PLUMBER'S PUTTY** can be rolled between the palms of your hands to form a long cord-like shape.
2. Lay out on the surface being sealed, overlapping the ends.
3. Place the fixture over the bead, attach and tighten down the fasteners from the fixture. Enough **TALON PLUMBER'S PUTTY** should be used so that some excess putty is squeezed out from all around the fixture ensuring that a continuous seal has been made.
4. Wipe of the excess. No additional sealer is needed.

## APPLICATION PRECAUTIONS

Do not use **TALON PLUMBER'S PUTTY** in direct contact with marble, granite or other porous stone, ceramics or manufactured substitutes.

Consult manufacturer. On natural materials (stone, marble, etc.) spray or brush contact area with clear acrylic lacquer and allow to dry. This prevents discoloration which might occur from putty components diffusing through the porous fixture. Then apply **TALON PLUMBER'S PUTTY**.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.  
Phone: 1-330-334-2524 • FAX 1-330-334-3005  
Email: [info@jcwhitlam.com](mailto:info@jcwhitlam.com)  
Website: [www.joinpipe.com](http://www.joinpipe.com)