

TALON OPEN MESH CLOTH

ALUMINUM OXIDE ABRASIVE SCREEN CLOTH

OM-SPEC

PRODUCT DESCRIPTION

PRODUCT

TALON OPEN MESH CLOTH Waterproof Aluminum Oxide Abrasive Screen Cloth

TYPE

TALON OPEN MESH CLOTH is a 180 grit, brown, waterproof, reusable, open meshed abrasive cloth made of high grade aluminum oxide, impregnated into a strong screen-type nylon mesh to help produce a tight, leak-proof solder joint. Open Mesh Cloth can be used on metal and plastic tubing and pipe. It is made with waterproof phenolic resin adhesive.

RECOMMENDED USES

TALON OPEN MESH CLOTH quickly cleans, deoxidizes and polishes solder joints prior to sweat soldering.

It is a completely waterproof abrasive cloth and is not affected by most oils and solvents. It will not fill up or become clogged, due to its open mesh design.

Both sides of this abrasive cloth can be used, giving it a longer useful life.

PACKAGING

U.S. Measure:

| <u>Stock Code</u> | <u>Size</u> |
|-------------------|---------------------------------------|
| Boxed | |
| OM5 | 1-1/2" x 5 yd. (3.81 cm x 4.54 m) |
| OM10 | 1-1/2" x 10 yd. (3.81 cm x 9.08 m) |
| OM25 | 1-1/2" x 25 yd. (3.81 cm x 22.7 m) |

SHIPPING WEIGHT PER CASE

| <u>Stock Code</u> | <u>Case Weight</u> | <u>#/Case</u> |
|-------------------|--------------------|---------------|
| OM5 | 14 lbs. (6.4 kg) | 50 |
| OM5A | 7 lbs. (3.2 kg) | 24 |
| OM10 | 23 lbs. (10.4 kg) | 50 |
| OM10A | 11 lbs. (5.0 kg) | 24 |
| OM25 | 21 lbs. (9.5 kg) | 20 |
| OM25A | 14 lbs. (6.4 kg) | 12 |

DIRECTIONS FOR USE

To use box as a dispenser:

1. Dispense 1-2 inches off the roll at the top of the box.
2. Close the lid.
3. Tear cloth to desired length.

MADE IN THE U.S.A.

OM-SPEC

© 2022 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.
Phone: 1-330-334-2524 • FAX 1-330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.