

# Product Information & Specifications

 **WHITLAM**  
**PAINT COMPANY**  
QUALITY COATINGS SINCE 1900  
P.O. Box 380 • Wadsworth, OH 44282  
800-321-8358 • [www.whitlampaint.com](http://www.whitlampaint.com)

**Product: PRO-STRIPE ATHLETIC FIELD MARKING PAINT**

**PSA-WHITE      PSA-RED**  
**PSA-YELLOW    PSA-HOT ORANGE**

## General Description

Specially formulated for line striping athletic fields. Engineered for use in an inverted position for quick and easy application with the Pro-Striper Turf Machine. Pro-Stripe Athletic Aerosol can be used in nearly all of our competitors marking machines due to our universal sprayhead design.

## Suggested Uses:

Baseball fields  
Football fields  
Soccer fields  
Volleyball courts  
Lawn & clay tennis courts  
Golf courses

## Benefits:

Makes 3"-6" wide stripes  
Ready for use in 30 minutes  
Sharp, well defined lines  
Good hide with one application  
One can will stripe approximately 300 feet  
V.O.C. Compliant - Water based  
Safe on grass and long lasting

## Additional Info:

Should be used with Pro-Striper Turf Machine and #705 Marking Wand.  
Compatible with most aerosol 4-wheeled marking machines currently On the market.

PRO-STRIPE ATHLETIC FIELD MARKING PAINT  
TECHNICAL INFORMATION

CONTAINER: 20 FLUID OUNCE AEROSOL CAN

LABEL WEIGHT: 18.0 OUNCES (511 GRAMS)

PROPELLANT: PROPANE N-BUTANE

CAN PRESSURE: 40 PSI @ 70<sup>0</sup>F

FLAMMABILITY: CLASSIFIED AS "EXTREMELY FLAMMABLE"

FLASH POINT: -4<sup>0</sup>F

% SOLIDS: @30%

DRY TIME: 15 MINUTES (QUICKER WHEN TEMPERATURE EXCEEDS 80<sup>0</sup>F)

V.O.C.: 46%, CANNOT EXCEED 66%

MIR VALUE: 0.61, CANNOT EXCEED 1.20

GLOSS: FLAT

CHEMICAL RESISTANCE: POOR

ADHESION: GOOD

DURABILITY: GOOD

APPLICATION TEMPERATURE: FOR BEST RESULTS: 40<sup>0</sup>-90<sup>0</sup>F

\*If the can is subjected to subfreezing temperatures, the can should be warmed to the operating temperature range (50F) before use to ensure a normal spray pattern. Do not use an open flame to warm the can.\*

HEAT RESISTANCE: 250<sup>0</sup>F

RESIN SYSTEM: V.T. ALKYD

ABRASION RESISTANCE: POOR

FLEXIBILITY: 1/4" MANDREL