

# All Weather Formula!

## PIPE SLIME™ PIPE GASKET LUBE

### USES:

A green viscous gasket lubricant for lubricating all rubber and plastic gaskets used in mechanical pipe coupling including, C900, C900/RJ™\*, SDR, HDPE, Polyethylene, Polypropylene, PVC and Ductile pipe and fittings. **PIPE SLIME™** insures proper alignment of gaskets for correct fit during pipe installation. It works well on wet or dry surfaces and is nontoxic and suitable for use on potable water systems. **PIPE SLIME™** is odorless and cleans up easily. Safe for use on all metal, plastic and rubber gasketed pipe. Excellent for jobs in all weather conditions.

\*C900/RJ™ is a CertainTeed Trademark

### COLOR/CONSISTENCY:

Lime Green Color/Smooth, thixotropic lubricant

### SPECIFICATIONS:

NSF Standard 61

### TEMPERATURE RANGE USE:

0°F (-18°C) to 150°F (66°C)

### AVAILABLE SIZES

Stock#	Size
SLIME32	Quart (.95 L)
SLIME1	Gallon (3.785 L)
SLIME5	5 Gallon (18.9 L)
SLIME55	55 Gallon (208 L)

J.C. Whitlam Manufacturing Co.  
P.O. Box 380 • Wadsworth, OH 44282  
U.S. & Canada



Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005

[www.pipeslime.com](http://www.pipeslime.com)

© 2021 J.C. Whitlam Manufacturing Co.

**PIPE SLIME™** is an emulsified polymer based lubricant that is specially formulated to prevent turbidity, taste, and/or odor problems in new water main installations. Independent tests performed by major municipalities have shown **PIPE SLIME™** will not promote turbidity, or transfer taste and odor, and completely flushes out of the system. **PIPE SLIME™** will not promote bacterial growth and is safe to use on all metal, plastic and rubber gasketed pipe.

- **Anti-Bacterial Formula**
- **Non-Reactive to Chlorine Solutions\***
- **Water Soluble**
- **Easily Flushes from the System**
- **Easy Cleanup**



### Advanced Formula:

**PIPE SLIME™** advanced formula allows for pre-lubricating of gaskets prior to assembly.



**Distributed By:**

**W WHITLAM**  
The Industry Standard for Over 100 Years

\*Avoid Direct Contact with Calcium Hypochlorite