

# SLUDGE•B•GONE

## FUEL OIL ADDITIVE

### SBG-SPEC

#### PRODUCT DESCRIPTION

##### PRODUCT

SLUDGE•B•GONE Fuel Oil Additive

##### DESCRIPTION

A premium, all season fuel oil treatment.

##### RECOMMENDED USES

SLUDGE•B•GONE is an excellent chemical treatment for cleaning burner orifices in oil burners; dissolving sludge and dissipating water in No. 1, 2, 3, 4, 5, 6 and bunker fuel oil tanks.

- PREVENTS CORROSION IN NO. 2 FUEL TANKS
- DISSOLVES SLUDGE
- DISPERSES WATER
- IMPROVES OIL FLOW
- PREVENTS FUEL LINE FREEZE-UP
- REDUCES SOOT
- STABILIZES SUMMER STORAGE

SLUDGE•B•GONE reduces fuel costs by dissolving sludge and rust in fuel oil tanks. Contains a special water dispersant to eliminate and prevent troublesome sludge by imparting a uniform consistency to fuel oils. Prevents ice freeze-ups by eliminating condensate water.

If used regularly, SLUDGE•B•GONE helps prevent clogging of strainers and nozzles. Clears fuel lines and prevents leaks by fighting corrosion. Reduces soot by increasing burner efficiency.

##### COLOR/CONSISTENCY

Clear Liquid

##### WEIGHT PER U.S. GALLON

8.2 lbs. (3.7 kg) ± 0.2

##### TEMPERATURE RANGE USE

0°F (-32°C) to 140°F (61°C)

##### SBG-SPEC

© 2022 J.C. Whitlam Manufacturing Company  
This product is manufactured in the U.S.A

#### APPLICATION PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. CONTAINS PETROLEUM DISTILLATES. MAY BE HARMFUL OR FATAL IF SWALLOWED. AVOID CONTACT WITH HANDS, FACE, AND EYES.

USE ONLY IN WELL VENTILATED AREA. KEEP AWAY FROM HEAT AND OPEN FLAME. COMBUSTIBLE MIXTURE.

FOR PROFESSIONAL USE ONLY.

SEE SAFETY DATA SHEET (SDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

##### ENVIRONMENTAL STATEMENT

SLUDGE•B•GONE prevents the formation of sludge to increase fuel oil burner efficiency and decrease fuel consumption.

##### PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
<b>Plastic Jug w/ Spout</b>	
SBG32	Quart (.95 L)
<b>Metal Can w/ Handle</b>	
SBG1	Gallon (3.785 L)

##### SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
SBG32	26 lbs. (11.8 kg)	12
SBG1	52 lbs. (23.6 kg)	4

#### DIRECTIONS FOR USE

1. Use one quart (.95L) of SLUDGE•B•GONE Fuel Oil Additive for a 275 gallon (1040L) tank, two quarts in a 550 gallon (2080L) tank, and one gallon (3.75L) per 1,000 gallon (3785L) capacity of fuel oil.

3. Agitation is necessary for best results. Treat by adding SLUDGE•B•GONE at the beginning of each heating season and immediately before delivery of oil.

3. For continued treatment, use one quart (.95 L) for each 1000 gallons (3785 L) consumed.

**FOR BEST RESULTS  
ADD JUST PRIOR TO OIL DELIVERY**

##### FOR REMOVING WATER CONDENSATE:

1. Use one quart (.95L) of SLUDGE•B•GONE Fuel Oil Additive for a 275 gallon (1040L) tank, two quarts in a 550 gallon (2080L), and one gallon (3.75L) per 1,000 gallon (3785L) capacity will remove condensation and help prevent ice formation in outside storage.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.  
Phone: 1-330-334-2524 • FAX 1-330-334-3005  
Email: [info@jcwhtlam.com](mailto:info@jcwhtlam.com)  
Website: [www.sludgebgone.com](http://www.sludgebgone.com)