## QUIK! RUST, LIME, CONCRETE AND SCALE REMOVER

QUIK! is recommended for dissolving rust, scale, and lime deposits on equipment and piping of plumbing, heating, processing, air conditioning, and water systems. QUIK! can also be used to remove deposits of carbonates, sulfates, phosphates, oxides, plaster and other organic deposits. QUIK! can be used on iron, copper, brass, bronze, steel, lead, plastic, china, and acid resistant enamelware.

DO NOT use QUIK! on aluminum, enamelware that is not acid resistant, magnesium, tin, nickel, zinc, chrome or galvanized metals. Where it is difficult to prevent QUIK! from coming in contact with these materials, coat surfaces with a thick coating of heavy grease or petroleum jelly.

QUIK! can be used to clear obstructions of plaster and concrete. QUIK! can also be used in HVAC systems as an anti-freeze preflush.

## **AVAILABLE SIZES:**

Stock#	Size
QK32	1 quart (.95 L)
QK1	1 gal. (3.785 Ĺ)

FOR PROFESSIONAL USE ONLY: **READ CAUTIONS AND FIRST AID PROCEDURES BEFORE USE. DO** NOT MIX WITH BLEACH OR AMMO-NIA. DO NOT APPLY TO CHROME **OR METAL FIXTURES. MUST WEAR** PROPER PROTECTIVE EQUIPMENT.

J.C. Whitlam Manufacturing Co. P.O. Box 380 • Wadsworth, OH 44282 U.S. & Canada Phone: 800-321-8358 FAX: 800-537-0588 International Phone: 330-334-2524 FAX: 330-334-3005

> www.jcwhitlam.com Email: info@jcwhitlam.com

STOCK CODE# QK32 CONTENTS 1 QUART 32 FL. OZ. (.951)

W

QUIK!

DANGER 👷 POISON

OUT OF REACH OF CHILDREN

Fast

Acting !!

Avoid

Breathing

**Distributed By:** 

Fumes

## FOR PROFESSIONAL USE ONLY! **NOT FOR RETAIL SALE**

- 35% Hydrochloric Acid
- Quickly Opens Urinals Eliminates Drain Odors
- **Cleans Rust and Scale**
- **Removes Concrete in Drains**

Read Cautions and First Aid Procedures before use. Always wear protective clothing. Rubber gloves and plastic safety goggles or face shield must be worn when using QUIK! **KEEP OUT OF REACH OF CHILDREN.** 

Removes rust, lime, concrete and scale from air conditioning equipment, refrigerator drains, water piping, boilers, water pump condensers, water sealed blowers, etc. Excellent for removing uretic salts in urinals. DO NOT use if lye, caustics or other chemicals are in the system. When opening container, place on flat surface. Hold bottle with one hand, push down and carefully unscrew cap taking care not to squeeze or tilt the bottle. Avoid splashing. When diluting QUIK! always pour acid into cold water and avoid splashing. Only use plastic container for mixing. Flush thoroughly with water immediately after using.





© 2022 J.C. Whitlam Manufacturing Co.