

## Safety Data Sheet

SDS ID: Stock Code #MP-YELLOW

Revision date: February 13, 2023

### Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** "Pro-Stripe" Yellow APWA Inverted Marking Paint

**Synonyms:** None

**Chemical family:** N/A

**Producer:** J.C. Whitlam Manufacturing Company

200 West Walnut Street

P.O. Box 380

Wadsworth, Ohio 44282-0380

[www.icwhitlam.com](http://www.icwhitlam.com)

**Telephone:** 330-334-2524 Available during normal business hours

**Emergency:** 330-334-2524 Available during normal business hours

### Section 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Pressurized container; protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn, even after use. Extremely flammable liquid and vapor. Keep away from heat, sparks and flame.

**GHS Label elements, including precautionary statements**

**DANGER** — Extremely Flammable; Pressurized Container

**WARNING** — Has narcotizing effect



DANGER



WARNING



GAS UNDER PRESSURE

**Precautionary Statements:** Keep locked up and out of the reach of children. Keep away from sources of ignition – No smoking. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

**Ingestion:** If swallowed, seek medical attention immediately and show the container or label.

### Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

#### Material information:

Name	CAS No.	Weight %
VM&P Naphtha	64742-89-8	18.98
Propane	74-98-6	17.64
Calcium Carbonate	1317-65-3	15.85
N-Butane	106-97-8	10.36
Mineral Spirits	64742-47-8	4.44

**\*Note:** The above weight percentages are represented in ranges as estimates. Due to variation among production batches, component percentages may vary.

**Section 4. FIRST AID MEASURES**

**Inhalation:** Supply fresh air; consult doctor in case of complaints.

**Skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.

**Ingestion:** Contact physician or poison control center.

**Eye contact:** Rinse opened eye for several minutes under running water, then consult a doctor.


**Section 5. FIREFIGHTING MEASURES**

**Suitable extinguishing media:** Carbon dioxide, sand, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**Specific hazards:** No further relevant information is available.

**Special protective equipment for firefighters:** No special measures required.

	NFPA rating:	HMIS rating:
Health:	1	1
Flammability:	3	3
Instability/reactivity:	3	3
Other:	N/A	H (PPE)



**Section 6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions:</b>	Wear protective equipment. Keep unprotected persons away.
<b>Large Spill:</b>	No data available.
<b>Methods for Containment and Clean up</b>	Do not allow product to reach sewage systems or ground water. Ensure adequate ventilation.

**Section 7. HANDLING AND STORAGE**

<b>Handling:</b>	Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.
<b>Storage:</b>	Observe pressurized container storage regulations. Consult with your local authorities.

## Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational Exposure Limits:

Name	CAS No.	ACGIH® TLV® Exposure Limits:	Federal OSHA PELs	OSHA PELs 1989 <sup>c</sup>
Propane	74-98-6	minimal oxygen content	1800 mg/m <sup>3</sup> 1000 ppm	N/A
N-Butane	106-97-8	2370 mg/m <sup>3</sup> 1000 ppm	N/A	N/A

**Engineering measures:** None.

### PERSONAL PROTECTIVE EQUIPMENT

**Respiratory protection:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Skin and body protection:** Wear protective gloves. The glove material must be impermeable and resistant to the substance. No glove recommendation can be given.

**Eye protection:** Tightly sealed goggles.

**Hygiene measures:** Keep away from food and animal feed. Wash hands after use.

**Other precautions:** N/A

## Section 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Yellow
<b>Physical state (solid/liquid/gas):</b>	Gas
<b>Substance type (pure/mixture):</b>	Mixture
<b>Color:</b>	Yellow
<b>Odor:</b>	Aromatic
<b>Molecular weight:</b>	Not available
<b>pH:</b>	Not determined
<b>Boiling point/range (5-95%):</b>	-47°F (-44°C)
<b>Melting point/range:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Specific gravity:</b>	Between 0.77 and 0.85 (water = 1)
<b>Vapor density:</b>	Not available
<b>Vapor pressure:</b>	40 PSI, 2750 hPa
<b>Evaporation rate (Butyl acetate= 1):</b>	Not available
<b>Flash point, method used:</b>	-2°F (-19°C)
<b>Water solubility:</b>	Not available
<b>VOC Content:</b>	528.8 g/l, 4.41 lb/gal
<b>Auto-ignition temperature:</b>	Product is not self-igniting
<b>Flammable limits in air — lower (%):</b>	1.5
<b>Flammable limits in air — upper (%):</b>	10.9

## Section 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	No data available
<b>Stability:</b>	Stable under recommended storage conditions.
<b>Possibly hazardous reactions:</b>	No data available
<b>Conditions to avoid:</b>	Do not allow can to exceed 120°F (49°C). Stable at normal temperatures.
<b>Incompatible Materials:</b>	Not available.
<b>Hazardous decomposition products:</b>	No dangerous decomposition products know.
<b>Polymerization:</b>	No data available.

## Section 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** Not available

**Chronic toxicity:** May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

**Sensitization:** No sensitizing effects know.

## Section 12. ECOLOGICAL INFORMATION

**Ecotoxicity effects:** Hazardous for water, do not empty into drains. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HFC's), perfluorocarbons (PFC's) or chlorinated solvents.

**Persistence** None

**Degradability:** None

## Section 13. DISPOSAL CONSIDERATIONS

**Cleanup considerations:** Disposal of this material must be done in accordance with federal, state and/or local regulations. Do not puncture, incinerate or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

## Section 14. TRANSPORT INFORMATION

UN-Number:	UN1950
DOT:	Consumer Commodity ORM-D AEROSOLS, Flammable
Class:	2.1
Marine Pollutant:	No
EMS Number:	F-D, S-U
Packaging Group:	N/A

## Section 15. REGULATORY INFORMATION

SARA Section 355: None of the ingredients in this product are listed.

SARA Section 313: None of the ingredients in this product are listed.

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1301 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer: ethyl benzene (100-41-4)

EPA: None of the ingredients are listed.

## Section 16. OTHER INFORMATION

### Standards and Certification Listings:

The information and recommendations contained herein are based upon tests, data, and information resources believed to be reliable. However, the J.C. Whitlam Manufacturing Company, Inc., and its related operations or divisions (Whitlam) do not guarantee the accuracy or completeness, nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of goods, the merchantability of the goods or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage may be required. Whitlam assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of this data. No warranty against infringement of any patent, copyright or trademark is made or implied.