

# LOW VOC CPVC CEMENT

## USAGE:

Solvent weld CPVC Flow-Guard Gold® pipe and fittings

## PIPE SIZE:

Through 2" (5.08 cm) diameter Sch. 80 CPVC pipe, C.T.S. (copper tube size) and potable water pressure pipe.

## PRESSURE RANGE USE:

### Liquids:

Up to 275 PSI (39.87 kPa)

## TEMPERATURE RANGE

### Use:

40°F (5°C) to 100°F (38°C)

## CONSISTENCY/COLOR:

Medium Bodied  
Yellow Colored Cement

## PARTIAL SET TIME:

Approx 45 seconds

## COMPLETE CURE TIME:

24 Hours

## SPECIFICATIONS:

Meets ASTM D2846,  
ASTM F493 and  
ASTM F3328-18

## AVAILABLE SIZES:

Stock#	Size
CPL4	¼ pint (118 ml)
CPL8	½ pint (237 ml)
CPL16	1 pint (473 ml)
CPL32	1 quart (.95 L)

J.C. Whitlam Manufacturing Co.  
P.O. Box 380  
Wadsworth, OH 44282  
U.S. & Canada  
Phone: 800-321-8358  
FAX: 800-537-0588  
International  
Phone: 330-334-2524  
FAX: 330-334-3005



# TALON



NSF Standard 14  
NSF Standard 61

## ONE STEP MEDIUM BODIED CEMENT APPROVED FOR

# FLOWGUARD GOLD® PIPE & FITTINGS

TALON LOW VOC CPVC YELLOW MEDIUM BODIED CEMENT is a smooth consistency, medium bodied cement formulated for use on small and medium solvent weld CPVC pipe and fittings in both cold and hot water applications.

- One Step Cement
- For Use on FlowGuard Gold® Pipe and Fittings
- Low VOC\* Formula
- No Primer Required\*\*

Distributed By:



The Industry Standard for Over 125 Years

\*Maximum VOC emissions as applied and tested per SCAQMD Rule 1168, Test Method 316A: less than 510 g/l

\*\*Use without primer when acceptable by local code.

FlowGuard Gold® is a Registered Trademark of the Lubrizol Corporation