

Go for the Green !

USAGE:

Solvent weld all classes of PVC solvent weld pipe and fittings.

PIPE SIZE:**Pressure Pipe:**

Up to 6" (15.24 cm)

Non-Pressure:

Up to 8" (20.32 cm)

PRESSURE RANGE USE:**Liquids:**

Up to 300 PSI (2068 kPa)

TEMPERATURE RANGE Use:

-20°F (-29°C) to 120°F (49°C)

CONSISTENCY/COLOR:

Medium Bodied

Green Colored Cement

SET TIME:

20 seconds

COMPLETE CURE TIME:

24 Hours

SPECIFICATIONS:

Meets ASTM D2564

Meets ASTM F3328

AVAILABLE SIZES:

Stock#	Size
IR4	¼ pint (118 ml)
IR8	½ pint (237 ml)
IR16	1 pint (473 ml)
IR32	1 quart (.95 L)
IR1	1 gal. (3.785 L)

J.C. Whitlam Manufacturing Co.
P.O. Box 380
Wadsworth, OH 44282
U.S. & Canada
Phone: 800-321-8358
FAX: 800-537-0588
International
Phone: 330-334-2524
FAX: 330-334-3005

2/2025



TALON™

PRO-GREEN FAST ONE-STEP LOW VOC* MEDIUM BODIED IRRIGATION PVC CEMENT



NSF Standard 14
NSF Standard 61

TALON PRO-GREEN One-Step** Irrigation Cement is a Fast Set, Low VOC, Medium Bodied Solvent Weld Cement specifically formulated for the irrigation and sprinkler contractor. Excellent for repair or everyday installations.

- **One-Step Cement**
- **Excellent for "Pulling" Pipe**
- **Works Well on Wet or Dry Pipe**
- **Great for Flexible PVC Pipe**
- **Allows for Immediate Pressure Testing**

Distributed By:

*Maximum VOC emissions as applied and tested per SCAQMD Rule 1168, Test Method 316A: less than 425 g/l

**Use without primer when acceptable by local code.

**Recommended as a One-Step Solvent Weld Cement for Drain, Waste and Vent (DWV) pipe and fittings in non-pressure applications in sizes up to 4" (10.16 cm) where acceptable by local code.



WHITLAM

The Industry Standard for Over 100 Years