



**Excellent for
Stainless
Connections**

WHITLAM

BLUE MAGIC INDUSTRIAL GRADE

Pipe Thread Compound

FOR USE ON THREADED:

PVC, CPVC, Delrin*, Zytel*,
Fiberglass, Nylon, Polypropylene,
Polybutylene, Polyethylene,
Celcon**, Cylolac***, and all types
of metal.

Approved for SPEARS® & IPEX
Fittings

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (211 kg/cm²)

Liquids:

Up to 6,000 PSI (422 kg/cm²)

TEMPERATURE RANGE USE:

-50°F (-46°C) to 400°F (204°C)

U.S. FEDERAL SPECIFICATIONS

Blue Magic exceeds TT-S-1732

AVAILABLE SIZES

| Stock# | Size |
|--------------------|----------------------|
| IG2 | 2 oz. tube (.056 kg) |
| IG4 | 1/4 pint (118 ml) |
| IG8 | 1/2 pint (237 ml) |
| IG8C ^a | 1/2 pint (237 ml) |
| IG16 | 1 pint (473 ml) |
| IG16C ^a | 1 pint (473 ml) |
| IG32 | 1 quart (.95 L) |
| IG5 | 5 gal. (18.9 L) |
| IG55 | 55 gal. (208 L) |

*Dupont registered trademarks

**Celanese registered trademark

***General Electric Plastics registered
trademark

^a Bi-lingual French/English label

BLUE MAGIC is an all purpose, non-seizing, PFAS-Free, industrial grade thread sealing compound that produces a leakproof seal on all types of plastic (including CPVC) and metal threaded connections. **BLUE MAGIC** is a smooth, grit free, completely homogenized, blue industrial grade paste.

- **Non-Separating**
- **Grit Free Paste**
- **Adheres to Oily Threads**
- **Non Combustible**
- **Safe for PVC & CPVC**
- **Nontoxic**
- **Superior Anti-Galling Properties**

Suitable for use on systems carrying:

| | | | |
|-------------------------|-----------------|--------------------|----------------|
| Acids, Dilute | Diesel Fuel Oil | Lacquer | Refrigeration |
| Air, Compressed | Fatty Acids | Mineral Oils | Gases |
| Aliphatic Solvents | Freons (All) | Naphtha | Soap, Liquid |
| Alkalis, Dilute | Gasohol | Natural Gas | Steam Lines |
| Ammonia | Gasoline | Nitrogen Gas | Sugar, Liquid |
| Brine | Glycol | Petroleum Oils | Vegetable Oils |
| Butane | Heating Oils | Petroleum Solvents | Water |
| Carbon Dioxide | Helium, Gaseous | Potable Water | Xylol |
| Castor Oils | Hydraulic Oils | Propane | |
| Caustic Alkali, Dilutes | Hydrogen | | |
| Chlorinated Water | Inert Gases | | |
| Coal Tar Naphtha | Jet Fuel | | |
| Corrosives | Kerosene | | |
| Cutting Oils | LP Gases | | |

"For a Positive Leakproof Seal"



NSF Standard 14
NSF Standard 61
pw-G/dww/sw



Underwriters'
Laboratories of Canada
Listed for Natural Gas,
Gasoline, Petroleum Oils,
Propane
& Butane

Distributed By:



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005



www.blue-magic.us
Email: info@jcwhitlam.com

© 2026 J.C. Whitlam Manufacturing Co.

04/2026

WHITLAM
The Industry Standard for Over 125 Years