

FOR USE ON THREADED:

PVC, CPVC, Delrin*, Zytel*, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon**, Cycolac***, and all types of metal. Approved for SPEARS® & IPEX Fittings

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (211 kg/cm²) Liquids:

Up to 6,000 PSI (422 kg/cm²)

TEMPERATURE RANGE USE: -50°F (-46°C) to 400°F (204°C)

U.S. FEDERAL SPECIFICATIONS

Blue Magic exceeds TT-S-1732

AVAILABLE SIZES

Stock# Size IG2 2 oz. tube (.056 kg) IG4 1/4 pint (118 ml) IG8 1/2 pint (237 ml) IG8C^a 1/2 pint (237 ml) IG16 1 pint (473 ml) IG16Ca 1 pint (473 ml) IG32 1 quart (.95 L) IG5 5 gal. (18.9 L) **IG55** 55 gal. (208 L)

*Dupont registered trademarks

**Celanese registered trademark

***General Electric Plastics registered trademark

J.C. Whitlam Manufacturing Co. P.O. Box 380 • Wadsworth, OH 44282



U.S. & Canada Phone: 800-321-8358 FAX: 800-537-0588 International

Phone: 330-334-2524 FAX: 330-334-3005

www.blue-magic.us Email: info@jcwhitlam.com

© 2025 J.C. Whitlam Manufacturing Co.

WHITLAM

BLUE MAGIC INDUSTRIAL GRADE

Pipe Thread Compound

BLUE MAGIC is an all purpose, non-seizing, PFAS– Free, industrial grade thread sealing compound that produces a leakproof seal on all types of plastic (including CPVC) and metal threaded connections. **BLUE MAGIC** is a smooth, grit free, completely homogenized, blue industrial grade paste.

- Non-Separating
- Grit Free Paste
- Adheres to Oily Threads
- Non Combustible
- Safe for PVC & CPVC
- Nontoxic
- Superior Anti-Galling Properties

Suitable for use on systems carrying:

Acids, Dilute
Air, Compressed
Aliphatic Solvents
Alkalis, Dilute
Ammonia
Brine
Butane
Carbon Dioxide
Castor Oils
Caustic Alkali, Dilutes
Chlorinated Water
Coal Tar Naphtha
Corrosives
Cutting Oils

Diesel Fuel Oil
Fatty Acids
Freons (All)
Gasohol
Gasoline
Glycol
Heating Oils
Helium, Gaseous
Hydraulic Oils
Hydrogen
Inert Gases
Jet Fuel
Kerosene
LP Gases

Lacquer
Mineral Oils
Naphtha
Natural Gas
Nitrogen Gas
Petroleum Oils
Petroleum Solvents
Potable Water
Propane

Refrigeration Gases Soap, Liquid Steam Lines Sugar, Liquid Vegetable Oils Water Xylol

"For a Positive Leakproof Seal"



NSF Standard 14 NSF Standard 61 pw-G/dwv/sw



Underwriters' Laboratories of Canada Listed for Natural Gas, Gasoline, Petroleum Oils, Propane & Butane

Distributed By:







^a Bi-lingual French/English label