

WHITLAM



BOILER-AIDE works excellent in Packaged Boilers. 1 gallon (3.785 L) will treat up to 160 gallons (605 L) of boiler water.

COLOR/CONSISTENCY:

Clear/Liquid

pH Concentrate 8.0

pH Solution 7.4 to 8.3

SPECIFIC GRAVITY:

1.1 g/L (± 0.1)

LOAD LEVEL:

The recommended in use concentration of the product is 0.6%. 1 quart (.95 L) will effectively treat 40 gallons (151.4 L) of boiler water.

Use **BOILER-AIDE 2-N-1 All Purpose Boiler Cleaner and Treatment** to clean sludge, grease and organic material during regular maintenance. Use Whitlam's **FLOW-AIDE** Biodegradable System Descaler to remove lime scale and improve boiler efficiency.

BOILER-AIDE outperforms the competition. After one week diluted to 0.6%.



X	Y	Z	BT	BT
New Fe and Cu fittings	New Fe and Cu fittings	New Fe and Cu fittings	Rusted Fe and Cu fittings	New Fe and Cu fittings

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, Ohio 44282

U.S. & Canada

Phone: 800-321-8358

Fax: 800-537-0588

International

Phone: +1-330-334-2524

Fax: +1-330-334-3005



10/2025
BT Flyer



BOILER-AIDE

2-N-1

ALL PURPOSE

Boiler Cleaner and Treatment

- Improves Boiler Efficiency
- Reduces Maintenance and Energy Cost
- Prevents Scale and Corrosion Buildup
- Nontoxic and Biodegradable
- Premium Boiler Treatment



BOILER-AIDE 2-N-1 All Purpose Boiler Cleaner and Treatment - A premium liquid boiler treatment with special anti-corrosion inhibitors used in all steam and hot water boilers. Protects boiler systems from corrosion, scale formation, and bacterial growth. This superior boiler water treatment removes sludge, mineral deposits, and inhibits corrosion on all metal surfaces inside the boiler and pipes. Prevents oxygen pitting and formation of lime scale; eliminates surging and foaming and controls pH of boiler water. **BOILER-AIDE** helps in increasing boiler efficiency and decreasing fuel consumption. Free from petroleum distillates and is compatible with seals and gaskets.

Stock Code	Size	Container	Items/Case	Case Weight
BT32	1 quart (.95 L)	Plastic Jug w/Spout	12	32 lbs. (14.5 kg)
BT1	1 gal. (3.785 L)	Plastic Jug w/Spout	6	57 lbs. (25.9 kg)
BT55	55 gal. (208.2 L)	55 Gallon Drum	1	500 lbs. (226.8 kg)

Distributed By:



www.Boiler-Aide.com

WHITLAM

The Industry Standard Over 100 Years