

CLEAR CLEANER PLASTIC PIPE CLEANER C-SPEC

PRODUCT DESCRIPTION

PRODUCT

CLEAR CLEANER Plastic Pipe Cleaner

TYPE

CLEAR CLEANER is a cleaner formulated for fast action in preparing plastic by removing any glaze which might be on the surface of the plastic and slightly softens the plastic so that it will readily accept the appropriate primer and solvent weld cement.

RECOMMENDED USES

CLEAR CLEANER is a cleaner for cleaning, deglazing and softening ABS, PVC and CPVC pipe and fittings prior to application of appropriate primer and cement.

COLOR/CONSISTENCY

Clear liquid.

TEMPERATURE RANGE USE

0°F (-18°C) to 100°F (38°C)

FOR USE ON THREADED:

ABS, PVC, CPVC pipe and fittings. Up through 12" (30.48 cm) diameter.

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
C4	¼ Pint (118 ml)
C8	½ Pint (237 ml)
C16	Pint (473 ml)
C32	Quart (.95 L)
C1	Gallon (3.785 L)

WEIGHT PER U.S. GALLON

6.75 lbs. (3.1 kg) ± 0.2

SHIPPING WEIGHT PER CASE

<u>Stock#</u>	<u>Case Weight</u>	<u>#/Case</u>
C4	9 lbs. (4.1 kg)	24/case
C8	15 lbs. (6.8 kg)	24/case
C16	14 lbs. (6.4 kg)	12/case
C32	25 lbs. (11.3 kg)	12/case
C1	50 lbs. (22.7 kg)	6/case

APPLICATION PRECAUTIONS

EXTREMELY FLAMMABLE !!!

**DO NOT USE NEAR HEAT,
SPARKS OR OPEN FLAME.**

**STORE IN COOL,
WELL VENTILATED AREA.**

**CONTAINS METHYL ETHYL KETONE.
HARMFUL OR FATAL IF SWALLOWED.**

**USE WITH ADEQUATE VENTILATION.
AVOID PROLONGED BREATHING OF
VAPORS. AVOID CONTACT WITH
EYES OR SKIN. KEEP CONTAINER
TIGHTLY CAPPED WHEN NOT IN USE.**

KEEP OUT OF REACH OF CHILDREN.

**SEE MATERIAL SAFETY DATA SHEET
(MSDS) FOR COMPLETE
PRECAUTIONS FOR SAFE HANDLING
AND USE.**

DIRECTIONS FOR USE

1. Check fitting of pipe. If too loose or too tight, pipe should not be used. Ideal fit between pipe and fitting before cementing allows pipe to enter to full depth of socket easily.
2. Remove all dust, moisture, grease, oil and any foreign material from pipe and fitting.
3. Apply generous amounts of **CLEAR CLEANER** to pipe and fitting. If surface is dry when ready to apply cement, apply additional **CLEAR CLEANER** so that cement is applied to a damp surface.
4. Keep container closed at all times when not using to avoid moisture absorption and vapor losses.
5. Follow all recommended procedures for joining plastic pipe and fittings as stated in ASTM D2855, D2235, and/or F493 where applicable.
6. **DO NOT USE THIS CLEANER TO THIN CEMENT.**

C-SPEC

©2005 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.



Division of
J.C. Whitlam Mfg. Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
website: www.jcwhitlam.com