

# WHITLAM

## LOW VOC CPVC CEMENT

### USAGE:

Solvent weld CPVC Flow-Guard Gold<sup>®</sup> pipe and fittings

### PIPE SIZE:

Through 2" (5.08 cm) diameter Sch. 80 CPVC pipe, C.T.S. (copper tube size) and potable water pressure pipe.

### PRESSURE RANGE USE:

#### Liquids:

Up to 275 PSI (39.87 kPa)

### TEMPERATURE RANGE

#### Use:

40°F (5°C) to 100°F (38°C)

### CONSISTENCY/COLOR:

Medium Bodied

Yellow Colored Cement

### PARTIAL SET TIME:

Approx 45 seconds

### COMPLETE CURE TIME:

24 Hours

### SPECIFICATIONS:

Meets ASTM D2846 and  
ASTM F493

### AVAILABLE SIZES:

Stock#	Size
CPL4	¼ pint (118 ml)
CPL8	½ pint (237 ml)
CPL16	1 pint (473 ml)
CPL32	1 quart (.95 L)

J.C. Whitlam Manufacturing Co.  
P.O. Box 380  
Wadsworth, OH 44282  
U.S. & Canada  
Phone: 800-321-8358  
FAX: 800-537-0588  
International  
Phone: 330-334-2524  
FAX: 330-334-3005

## YELLOW MEDIUM BODIED CEMENT APPROVED FOR

### **FLOWGUARD GOLD<sup>®</sup>** PIPE & FITTINGS



**WHITLAM LOW VOC CPVC YELLOW MEDIUM BODIED CEMENT** is a smooth consistency, medium bodied cement formulated for use on small and medium solvent weld CPVC pipe and fittings in both cold and hot water applications.

- One Step Cement
- For use on FlowGuard Gold<sup>®</sup> pipe and fittings
- Low VOC\* Formula
- No Primer Required\*\*

\*Maximum VOC emissions as applied and tested per SCAQMD Rule 1168, Test Method 316A: 250 g/l  
\*\*Use without primer when acceptable by local code.

Distributed By:

 **WHITLAM**  
**PLUMB-PRO**  
The Industry Standard for Over 100 Years  
[whitlam-plumbpro.com](http://whitlam-plumbpro.com)