

REACH LUBE OIL LO-SPEC

PRODUCT DESCRIPTION

PRODUCT

REACH Lube Oil

TYPE

REACH Lube Oil is a clear, high quality lubricating oil that also cleans and preserves metal.

REACH Lube Oil contains rust and oxidation inhibitors, which help prevent scoring of bearings and sticking of close fitting components. Formula has excellent anti-foam and air release characteristics. Non-Detergent. Non-Toxic.

Special telescoping spout allows easy access to hard to reach spots.

RECOMMENDED USES

REACH Lube Oil can be used for lubricating wherever metal lubrication is needed:

Excellent for use on:

- Electrical Motors
- Steam and Gas Turbines
- Hydraulic Circulating Pumps
- Hydraulic Systems
- Air Compressors
- Bearings
- Fans
- Farm Equipment
- Automobiles
- Appliances
- Generators
- Machine Tools
- Hinges
- Etc.

PHYSICAL PROPERTIES

SAE:	20
Specific Gravity° API:	29.5
Flash Point, COC:	415° F (212° C)
Pour Point:	-10° F (-23° C)
Viscosity cSt at 40°C:	64.7
Viscosity Index:	96

COLOR/CONSISTENCY

Clear oil.

LO-SPEC

© 2005 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

PACKAGING

U.S. Measure:

Plastic Bottle w/ Pull Out Spout
LO4 4 fl. oz. (118 ml)

WEIGHT PER U.S. GALLON

7.35 lbs. (3.31 kg) ± 0.2

SHIPPING WEIGHT PER CASE

Stock#	Case Weight	#/Case
LO4	7 lbs. (3.2 kg)	24/case

DIRECTIONS FOR USE

FOR OIL PUMPS AND MOTORS:

1. Invert container; squeeze apportioned amount (#3 mark on container) into bearing assembly cup first. (Stop if oil overflows.)

2. For motor cups two and one use corresponding marks (#2 and #1). (Corresponding marks on the side of the container.)

3. Use remaining oil as an all purpose lubricant.

DO NOT USE ON EXTREME HEAT PRODUCING OPERATIONS.

SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.



Division of
J.C. Whitlam Mfg. Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
website: www.jcwhitlam.com