

MAKE-TYTE SUPER SOFT STAINLESS PLUMBER'S PUTTY MT-SPEC

PRODUCT DESCRIPTION

PRODUCT

MAKE TYTE Super Soft Stainless Plumber's Putty.

TYPE

MAKE-TYTE is a pliable non-hardening putty for sealing rims of faucets, sinks, strainers, etc. Never cracks, hardens, dries out or mildews. **MAKE-TYTE** sticks to metal, plastic, fiberglass and wood, but not to your hands.

MAKE-TYTE is flexible and stretchable, spreads easily, and can be molded into rings or shaped to the precise configuration needed. It provides a gas proof, fume proof, odor proof, insect proof and watertight seal.

RECOMMENDED USES

Used for setting bowls, fixtures, faucets, basin cocks, strainers, plugs, sink frames as well as many other sealing and caulking jobs.

PHYSICAL PROPERTIES

Specific Gravity: 1.97 ±0.2
Solubility in water: Insoluble

COLOR/CONSISTENCY

Off White. Heavy paste to be applied by hand or putty knife.

TEMPERATURE RANGE USE

-50°F (-45°C) to 140°F (60°C).

Application:

40°F (4°C) to 100°F (37°C).

MT-SPEC

© 2005 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

APPROVALS AND LISTINGS

Meets or exceeds Federal Specifications TT-P-1536A.

ENVIRONMENTAL STATEMENT

MAKE-TYTE is classified as non-hazardous as defined by OSHA 29 CFR 1910.1200

PACKAGING

U.S. Measure:

Stock Code	Size
MT1	14 oz (.4 kg)
MT3	3 lbs (1.4 kg)
MT5	5 lbs (2.3 kg)
MT15	15 lbs (6.8 kg)

WEIGHT PER U.S. GALLON

16.27 lb/gal (7.38 kg) ±0.2

SHIPPING WEIGHT PER CASE

Stock#	Case Weight	#/Case
MT1	14 oz (.4 kg)	24/case
MT3	3 lbs (1.4 kg)	6/case
MT5	5 lbs (2.3 kg)	6/case
MT15	15 lbs (6.8 kg)	4/case

DIRECTIONS FOR USE

1. Take out required amount and form the putty to the approximate shape needed. **MAKE-TYTE** can be rolled between the palms of your hands to form a long cord-like shape.
2. Lay out on the surface being sealed, overlapping the ends.
3. Place the fixture over the bead, attach and tighten down the fasteners from the fixture. Enough **MAKE-TYTE** should be used so that some excess putty is squeezed out from all around the fixture ensuring that a continuous seal has been made.
4. Wipe of the excess. No additional sealer is needed.

APPLICATION PRECAUTIONS

Do not use **MAKE-TYTE** in direct contact with marble, granite or other porous stone, ceramics or manufactured substitutes.

Consult manufacturer. On natural materials (stone, marble, etc.) spray or brush contact area with clear acrylic lacquer and allow to dry. This prevents discoloration which might occur from putty components diffusing through the porous fixture. Then apply **MAKE-TYTE**.



Division of
J.C. Whitlam Mfg. Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
website: www.jcwhitlam.com