

OPEN MESH CLOTH ALUMINUM OXIDE ABRASIVE SCREEN CLOTH OM-SPEC

PRODUCT DESCRIPTION

PRODUCT

OPEN MESH CLOTH Waterproof Aluminum Oxide Abrasive Screen Cloth

TYPE

OPEN MESH CLOTH is a 180 grit, brown, waterproof, reusable, open meshed abrasive cloth made of high grade aluminum oxide, impregnated into a strong screen-type nylon mesh to help produce a tight, leakproof solder joint. Open Mesh Cloth can be used on metal and plastic tubing and pipe. It is made with waterproof phenolic resin adhesive.

RECOMMENDED USES

OPEN MESH CLOTH quickly cleans, deoxidizes and polishes solder joints prior to sweat soldering.

It is a completely waterproof abrasive cloth and is not affected by most oils and solvents. It will not fill up or become clogged, due to its open mesh design.

Both sides of this abrasive cloth can be used, giving it a longer useful life.

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Boxed	
OM5	1-1/2" x 5 yd. (3.81 cm x 4.54 m)
OM10	1-1/2" x 10 yd. (3.81 cm x 9.08 m)
OM25	1-1/2" x 25 yd. (3.81 cm x 22.7 m)

SHIPPING WEIGHT PER CASE

<u>Stock#</u>	<u>Case Weight</u>	<u>#/Case</u>
OM5	14 lbs. (6.4 kg)	50/case
OM5A	7 lbs. (3.2 kg)	24/case
OM10	23 lbs. (10.4 kg)	50/case
OM10A	11 lbs. (5.0 kg)	24/case
OM25	21 lbs. (9.5 kg)	20/case
OM25A	14 lbs. (6.4 kg)	12/case

DIRECTIONS FOR USE

To use box as a dispenser:

1. Dispense 1-2 inches off the roll at the top of the box.
2. Close the lid.
3. Tear cloth to desired length.

SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

MADE IN THE U.S.A.

OM-SPEC

© 2007 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.



Division of
J.C. Whitlam Manufacturing Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
Website: www.jcwhitlam.com

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.