

QUIK ! HYDROCHLORIC ACID (HCL) RUST, LIME, CONCRETE and SCALE REMOVER QK-SPEC

PRODUCT DESCRIPTION

PRODUCT

QUIK ! RUST, LIME, CONCRETE and SCALE REMOVER

TYPE

QUIK ! is a scientifically blended formulation of hydrochloric acid, metal protecting inhibitors and a strong anti-foam suppressant.

FOR PROFESSIONAL USE ONLY !

NOT FOR RETAIL SALE.

RECOMMENDED USES

QUIK ! is recommended for dissolving rust, scale, and lime deposits on equipment and piping of plumbing, heating, processing, air conditioning, and water systems. QUIK ! can also be used to remove deposits of carbonates, sulfates, phosphates, oxides, plaster and other organic deposits. QUIK ! can be used on iron, copper, brass, bronze, steel, lead, plastic, china, and acid resistant enamelware.

Do not use QUIK ! on aluminum, enamelware that is not acid resistant, magnesium, tin, nickel, zinc, chrome or galvanized metals. Where it is difficult to prevent QUIK ! from coming in contact with these materials, coat surfaces with a thick coating of heavy grease or petroleum jelly.

QUIK ! can be used to clear obstructions of plaster and concrete. QUIK ! can also be used in HVAC systems as an anti-freeze preflush.

COLOR/CONSISTENCY

Red Liquid

WEIGHT PER U.S. GALLON

9.7 lbs. (4.4 kg) ± 0.2

QK-SPEC

© 2005 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

APPLICATION PRECAUTIONS

WARNING:

DANGER



POISON

READ ENTIRE PRODUCT LABEL AND MATERIAL SAFETY DATA SHEET BEFORE USING PRODUCT. QUIK ! RUST, LIME, CONCRETE and SCALE REMOVER CONTAINS HYDROCHLORIC ACID. HIGHLY CORROSIVE. CAUSES SEVERE BURNS AND/OR BLINDNESS. HARMFUL OR FATAL IF SWALLOWED. DO NOT MIX WITH BLEACH, ALKALINE OR OTHER CHEMICALS.

KEEP AWAY FROM CHILDREN.

ALWAYS WEAR RUBBER GLOVES AND GOGGLES OR FACE SHIELD WHEN HANDLING QUIK !

DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.

DO NOT BREATHE VAPORS OR MIST. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROVIDE SUFFICIENT VENTILATION TO PREVENT BUILDUP OF VAPORS OR MIST.

WASH THOROUGHLY AFTER HANDLING, INCLUDING CONTAMINATED EQUIPMENT, SHOES AND CLOTHING.

ALWAYS ADD ACID TO WATER TO MAKE PROPER DOSAGE. NEVER ADD WATER TO ACID.

STORE IN A COOL DRY PLACE AND AWAY FROM OXIDIZING AGENTS. KEEP CONTAINER CLOSED AND TIGHTLY CAPPED. DO NOT DROP. AVOID SPILLS - THIS PRODUCT WILL ATTACK ALL ORGANIC MATERIAL. USE ORIGINAL CONTAINER ONLY. DO NOT TRANSFER.

(CONTINUED ON NEXT COLUMN)

APPLICATION PRECAUTIONS

WHEN CONTAINER IS COMPLETELY EMPTY, RINSE CAREFULLY WITH COLD WATER BEFORE DISCARDING TO PREVENT ACCIDENTAL BURNS.

FOR SALE TO, USE AND STORAGE BY PROFESSIONALS ONLY ! NOT FOR CONSUMER USE.

PACKAGING

U.S. Measure:

Stock Code	Size
QK32	1 quart (.95 L)
QK1	1 gal. (3.785 L)

SHIPPING WEIGHT PER CASE

Stock #	Case Weight	#/Case
QK32	34 lbs. (15.4 kg)	12/case
QK1	40 lbs. (18.1 kg)	4/case

DIRECTIONS FOR USE

1. Always wear protective clothing. Rubber gloves and plastic safety goggles or face shield must be worn when using QUIK !
2. DO NOT use if lye, caustics or other chemicals are in the system.
3. When opening container, place on flat surface. Hold bottle with one hand, push down and carefully unscrew cap taking care not to squeeze or tilt the bottle. Avoid splashing.
4. Determine what concentration of QUIK ! to use by the table on reverse side of this sheet.
5. When diluting QUIK !, always pour acid into cold water and avoid splashing. Only use plastic container for mixing.
6. Flush thoroughly with water immediately after using.

(over)

 **WHITLAM**
PLUMB-PRO
The Industry Standard for Over 100 Years

Division of
J.C. Whitlam Mfg. Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
website: www.jcwhitlam.com

QUIK ! HYDROCHLORIC ACID (HCL) RUST, LIME, CONCRETE and SCALE REMOVER QK-SPEC

CAUTION:

READ DIRECTIONS ON LABEL BEFORE USING.

ALWAYS ADD ACID TO WATER TO MAKE PROPER DOSAGES.

NEVER ADD WATER TO ACID.

USES	RECOMMENDED DOSAGE
Boilers	1 part QUIK ! to 10 to 15 parts water.
Gas Water Heaters	1 gallon QUIK ! to 4 gallons of water for each 25 gallons of heater capacity.
Hot Water Coils	1 part QUIK ! to 2 parts water.
Cooling Towers, Condensers & Heat Exchangers	1 gallon QUIK ! for each 20 gallons of water in the system.
Unit Heaters	1 part QUIK ! to 2 parts water. If circulating pump is used, reduce strength to 1 part QUIK ! to 4 parts water.
Urinals & Toilet Bowls (Sanitary Maintenance)	Undiluted QUIK ! as needed. Allow to stand 15 minutes, then flush.
Concrete & Plaster Obstructions	Undiluted QUIK ! as needed. Flush with cold water.
China & Acid Resistant Enamels (Stains)	Undiluted QUIK ! Dilute depending on degree of stain.

QK-SPEC

© 2005 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.



Division of
J.C. Whitlam Mfg. Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
website: www.jcwhitlam.com

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.