

# SLUDGE•B•GONE (SBG) FUEL OIL ADDITIVE SBG-SPEC

## PRODUCT DESCRIPTION

### PRODUCT

SLUDGE•B•GONE Fuel Oil Additive

### TYPE

A premium, all season fuel oil treatment.

### RECOMMENDED USES

SLUDGE•B•GONE is an excellent chemical treatment for cleaning burner orifices in oil burners; dissolving sludge and dissipating water in No. 2 fuel oil.

### SLUDGE•B•GONE:

- PREVENTS CORROSION IN NO. 2 FUEL TANKS
- DISSOLVES SLUDGE
- REMOVES WATER
- IMPROVES OIL FLOW
- PREVENTS FUEL LINE FREEZE-UP
- REDUCES SOOT
- STABILIZES SUMMER STORAGE

SLUDGE•B•GONE reduces fuel costs by dissolving sludge and rust in No. 2 fuel oil tanks. Contains a special water dispersant to eliminate and prevent troublesome sludge by imparting a uniform consistency to fuel oils. Prevents ice freeze-ups by eliminating condensate water. If used regularly, SLUDGE•B•GONE helps prevent clogging of strainers and nozzles. Clears fuel lines and prevents leaks by fighting corrosion. Reduces soot by increasing burner efficiency.

### COLOR / CONSISTENCY

Clear/Liquid

### SBG-SPEC

©2005 J.C. Whitlam Manufacturing Company  
This product is manufactured in the U.S.A.

## ENVIRONMENTAL STATEMENT

SLUDGE•B•GONE prevents the formation of sludge to increase fuel oil burner efficiency and decrease fuel consumption.

## APPLICATION PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. CONTAINS PETROLEUM DISTILLATES. MAY BE HARMFUL OR FATAL IF SWALLOWED. AVOID CONTACT WITH HANDS, FACE, AND EYES.

USE ONLY IN WELL VENTILATED AREA. KEEP AWAY FROM HEAT AND OPEN FLAME. COMBUSTIBLE MIXTURE.

FOR PROFESSIONAL USE ONLY.

SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

## TEMPERATURE RANGE USE

0°F (-32°C) TO 140°F (61°C)

## PACKAGING

### U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Plastic Jug w/ Spout SBG32	1 qt. (.95 L)
Metal Can w/ Handle SBG1	1 gal.(3.785 L)

### WEIGHT PER U.S. GALLON

8.2 lbs. (3.7 kg) ± 0.2

### SHIPPING WEIGHT PER CASE

<u>Stock#</u>	<u>Case Weight</u>	<u>#/Case</u>
SBG32	26 lbs. (11.8 kg)	12/case
SBG1	35 lbs. (15.9 kg)	4/case

## DIRECTIONS FOR USE

### FOR REMOVING SLUDGE:

1. Add one quart (.95 L) for each 250 gallons (946 L) of fuel oil.
2. For continued treatment, use one quart (.95 L) for each 1000 gallons (3785 L) consumed.

### FOR BEST RESULTS ADD JUST PRIOR TO OIL DELIVERY

### FOR REMOVING WATER CONDENSATE:

1. Two quarts of SLUDGE•B•GONE Fuel Oil Additive in a 550 gallon (2080 L) tank will remove condensation and help prevent ice formation in outside storage.

2. Treat fuel oil by adding SLUDGE•B•GONE at the beginning of each heating season.



Division of  
J.C. Whitlam Mfg. Company  
P.O. Box 380  
Wadsworth, Ohio 44282  
Phone: 330-334-2524  
Fax: 330-334-3005  
email: info@jcwhitlam.com  
website: www.jcwhitlam.com