

TUB-TYTE

ALL PURPOSE SILICONIZED ACRYLIC CAULK AND ADHESIVE

TTC, TTL, TTW-SPEC

PRODUCT DESCRIPTION

PRODUCT

TUB-TYTE All Purpose Siliconized Acrylic Caulk and Adhesive.

TYPE

TUB-TYTE is a mildew resistant, paintable sealant formulated to provide long lasting, flexible, weatherproof seals between most common building materials including wood, masonry, concrete, drywall, metal, glass, and tile. Special smooth consistency formula makes caulk easy to use and cures to a tough, flexible seal on both exterior and interior surfaces.

Completely water resistant once cured. Will not mildew, crack or shrink. 35 year durability. Stays flexible and elastic for over 10 years.

Available in clear, biscuit/linen and white.

RECOMMENDED USES

Use to fill cracks in walls, woodwork and loose tiles. Especially effective around tubs, sinks, and shower stalls.

Eliminates leaks and drafts around doors, windows, siding joints, vents and basement seams.

Firmly attaches self-rimming sinks; adheres to plastic, ceramic, glass, wood and masonry surfaces, faucets, tile, and also is an excellent adhesive for paneling.

COLOR/CONSISTENCY

Comes in three colors: Clear (TTC), Biscuit/Linen (TTL) and White (TTW) Paste.

TEMPERATURE RANGE USE

40°F (4°C) to 95°F (35°C)

After Curing:
-50°F (-45°C) to 180°F (82°C)

TTC, TTL, TTW-SPEC

© 2005 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

DRYING TIME

Set up time is 10-30 minutes.

Cures completely within 12-24 hours.

U.S. FEDERAL SPECIFICATIONS

Meets or exceeds ASTM C834.
VOC 24 GPL.

APPLICATION PRECAUTIONS

CONTAINS ETHYLENE GLYCOL AND PETROLEUM DISTILLATES.

KEEP OUT OF REACH OF CHILDREN.

SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

PACKAGING

U.S. Measure:

Stock Code	Size
Plastic Tube	
TTC5	5.5 fl. oz. (162 ml)
TTL5	5.5 fl. oz. (162 ml)
TTW5	5.5 fl. oz. (162 ml)

Cartridge

TTC10	10.1 fl. oz. (300 ml)
TTL10	10.1 fl. oz. (300 ml)
TTW10	10.1 fl. oz. (300 ml)

WEIGHT PER U.S. GALLON

12.8 lbs. (5.8 kg) ±0.2

SHIPPING WEIGHT PER CASE

Stock#	Case Weight	#/Case
TTC5	8 lbs. (3.6 kg)	12/case
TTL5	8 lbs. (3.6 kg)	12/case
TTW5	8 lbs. (3.6 kg)	12/case
TTC10	15 lbs. (6.8 kg)	12/case
TTL10	15 lbs. (6.8 kg)	12/case
TTW10	15 lbs. (6.8 kg)	12/case

DIRECTIONS FOR USE

Tube:

1. Knead tube before using.
2. Remove all loose material. Use rubbing alcohol to remove soil from tubs, tiles, and sinks.
3. Clean and dry surfaces thoroughly.
4. Cut spout at an angle for desired bead size.
5. Apply a bead of **TUB-TYTE** to the surface to be sealed.
6. Remove excess with damp cloth before it dries.
7. Tools and hands are easily cleaned with soapy water.

Cartridge:

1. Clean and dry surfaces thoroughly.
2. Remove all loose material. Use rubbing alcohol to remove soil from tubs, tiles, and sinks.
3. Fill deep joints or voids with solid filler to ½" of surface.
4. Cut nozzle to desired bead size.
5. Puncture inner seal and insert cartridge into caulking gun.
6. For a smooth seal, hold at 45° angle and apply by pushing **TUB-TYTE** ahead of nozzle.
7. Excess material can be smoothed with a putty knife or cleaned with a damp cloth.
8. Allow a minimum of 2 hours dry time before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and/or cool temperatures.
9. For best results apply at 40°F (4°C) or above.



Division of
J.C. Whitlam Mfg. Company
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
email: info@jcwhitlam.com
website: www.jcwhitlam.com