

Meets ASTM B-813

WHITLAM AQUA-PRO 2000

USAGE

Solder Flux for use with 95/5, 60/40, 50/50, 40/60 and Lead Free Solders on Copper, Copper Alloy, Brass, Galvanized Iron, Tin, Steel, Terne Plate, Zinc, Silver, Nickel and Sheet Lead.

TEMPERATURE RANGE

Use:

0°F (-18°C) to 130°F (54°C)

Melting Temperature:

140°F (72°C)

CONSISTENCY/COLOR

Paste / Gold

AMERICAN SOCIETY FOR TESTING AND MATERIALS SPECIFICATION

Meets ASTM B-813

U.S. FEDERAL SPECIFICATIONS

AQUA-PRO 2000 meets
506 C Type 1 Form A

AVAILABLE SIZES

Stock#	Size
WF2	2 oz. (57 g)
WF4	4 oz. (113.4 g)
WF1	1 lb. (454 g)

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282

U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005



- **Water Soluble**
- **Fast Drawing**
- **High Melt Point**
- **Non-Fuming**
- **Non-Corrosive**
- **Self-Cleaning Formula**
- **Convenient Screw-Top Lid**
- **Zinc Chloride and Lead Free**

AQUA-PRO 2000, water soluble paste flux is a specially formulated, Water Soluble, Water Flushable Solder Flux for use with 95/5, 60/40, 50/50, 40/60 and Lead Free Solders on Copper, Copper Alloys, Brass, Galvanized Iron, Tin, Steel, Terne Plate, Zinc, Silver, Nickel and Sheet Lead

WHITLAM
PLUMB-PRO
The Industry Standard for Over 100 Years
www.whitlam-plumbpro.com