

# WHITLAM

# BLUE MAGIC INDUSTRIAL GRADE

## Pipe Thread Compound

**BLUE MAGIC** is an all purpose, non-seizing, industrial grade thread sealing compound that produces a leakproof seal on all types of plastic and metal (including stainless steel) threaded connections. **BLUE MAGIC** is a smooth, grit free, completely homogenized, blue industrial grade paste.

- Non-Separating
- Grit Free Paste
- Adheres to Oily Threads
- Non Combustible
- Safe for PVC & CPVC
- Nontoxic
- Superior Anti-Galling Properties

### Suitable for use on systems carrying:

Acids, Dilute	Diesel Fuel Oil	Lacquer	Refrigeration
Air, Compressed	Fatty Acids	Mineral Oils	Gases
Aliphatic Solvents	Freons (All)	Naphtha	Soap, Liquid
Alkalis, Dilute	Gasohol	Natural Gas	Steam Lines
Ammonia	Gasoline	Nitrogen Gas	Sugar, Liquid
Brine	Glycol	Petroleum Oils	Vegetable Oils
Butane	Heating Oils	Petroleum Solvents	Water
Carbon Dioxide	Helium, Gaseous	Potable Water	Xylol
Castor Oils	Hydraulic Oils	Propane	
Caustic Alkali, Dilutes	Hydrogen		
Chlorinated Water	Inert Gases		
Coal Tar Naphtha	Jet Fuel		
Corrosives	Kerosene		
Cutting Oils	LP Gases		

### FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin\*, Zytel\*,  
Fiberglass, Nylon, Polypropylene,  
Polybutylene, Polyethylene,  
Celcon\*\*, Cyclocac\*\*\*, and all  
types of metal.

Approved for SPEARS® & IPEX  
Fittings

### PRESSURE RANGE USE:

#### Gases:

Up to 3,000 PSI (211 kg/cm<sup>2</sup>)

#### Liquids:

Up to 6,000 PSI (422 kg/cm<sup>2</sup>)

### TEMPERATURE

#### RANGE USE:

-50°F (-46°C) to 400°F (+204°C)

### U.S. FEDERAL SPECIFICATIONS

Blue Magic exceeds TT-S-1732

### AVAILABLE SIZES

Stock#	Size
IG2	2 oz. tube (.056 kg)
IG4	1/4 pint (118 ml)
IG8	1/2 pint (237 ml)
IG8A†	1/2 pint (237 ml)
IG16	1 pint (473 ml)
IG32	1 quart (.95 L)
IG1	1 gal. (3.785 L)
IG5	5 gal. (18.9 L)
IG55	55 gal. (208 L)

\*Dupont registered trademarks

\*\*Celanese registered trademark

\*\*\*General Electric Plastics registered  
trademark

† IG8A is packaged in a display box

J.C. Whitlam Manufacturing Co.  
P.O. Box 380 • Wadsworth, OH 44282  
U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

#### International

Phone: 330-334-2524

FAX: 330-334-3005

[www.joinpipe.com](http://www.joinpipe.com)

Email: [info@jcwhitlam.com](mailto:info@jcwhitlam.com)



NSF Standard 14  
NSF Standard 61  
pw-G/dww/sw



Underwriters'  
Laboratories of Canada  
Listed for Natural Gas,  
Gasoline, Petroleum Oils,  
Propane & Butane

"For a Positive Leakproof Seal"

Distributed By:



**WHITLAM**  
**PLUMB-PRO**  
The Industry Standard for Over 100 Years