

# WHITLAM POWER SEAL



## Thread Sealing Compound

**POWER SEAL PLUS** is specially formulated for the fire protection industry for use on all metal threaded connections, **FlowGuard Gold®**, **Blazemaster®**, and **Corzan®** pipe and fittings.



### SYSTEM COMPATIBLE

- Non-Separating
- Grit Free Paste
- Non-Hardening
- Non-Toxic
- Easy Cleanup
- Indefinite Shelf Life
- Adheres to Oily Threads

### TEMPERATURE RANGE USE:

#### Gases:

-15°F (-26°C) to 400°F (204°C)

#### Liquids:

-15°F (-26°C) to 400°F (204°C)

Brushable to -15°F (-26°C)

### PRESSURE RANGE USE:

#### Gases:

Up to 5,000 PSI (351.5 kg/cm<sup>2</sup>)

#### Liquids:

Up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)

### U.S. FEDERAL

#### SPECIFICATIONS:

Power Seal Plus exceeds TT-S-1732

### AVAILABLE SIZES:

Stock#	Size
Brush Top Can	
POW16B	1 pint (473 ml)
POW32B	1 quart (.95 L)
Flat Top Can	
POW16	1 pint (473 ml)
POW32	1 quart (.95 L)
POW1	1 gal. (3.785 L)
Pail	
POW5	5 gal. (18.9 L)
Drum	
POW55	55 gal. (208 L)

FGG/BM/CZ™ System Compatible indicates that POWER SEAL PLUS has been tested, and is monitored on an ongoing basis, to assure chemical compatibility with FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings. FGG/BM/CZ™ FlowGuard Gold®, Blazemaster®, and Corzan® are licensed trademarks of the Lubrizol Corporation.

J.C. Whitlam Manufacturing Co.  
P.O. Box 380  
Wadsworth, OH 44282  
U.S. & Canada  
Phone: 800-321-8358  
FAX: 800-537-0588  
International  
Phone: 330-334-2524  
FAX: 330-334-3005

### Suitable for use on systems carrying:

Acids, Dilute; Air; Aliphatic Solvents; Alkalis, Dilute; Ammonia; Glycol; LP Gases; Natural Gas; Refrigeration Gases; Steam; Water.

Distributed By:

 **WHITLAM**  
**PLUMB-PRO**  
The Industry Standard for Over 100 Years  
**PowerSealPlus.com**