

# WHITLAM POWER SEAL



## Thread Sealing Compound

**POWER SEAL PLUS** is specially formulated for the fire protection industry for use on all metal threaded connections, **FlowGuard Gold®**, **Blazemaster®**, and **Corzan®** pipe and fittings.

### TEMPERATURE RANGE USE:

#### Gases:

-15°F (-26°C) to 400°F (204°C)

#### Liquids:

-15°F (-26°C) to 400°F (204°C)

Brushable to -15°F (-26°C)

### PRESSURE RANGE USE:

#### Gases:

Up to 5,000 PSI (351.5 kg/cm<sup>2</sup>)

#### Liquids:

Up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)

### U.S. FEDERAL SPECIFICATIONS:

Power Seal exceeds TT-S-1732

### AVAILABLE SIZES:

Stock#	Size
Brush Top Can	
POW16B	1 pint (473 ml)
POW32B	1 quart (.95 L)
Flat Top Can	
POW16	1 pint (473 ml)
POW32	1 quart (.95 L)
POW1	1 gal. (3.785 L)
Pail	
POW5	5 gal. (18.9 L)
Drum	
POW55	55 gal. (208 L)

"FBC™ System Compatible indicates that this product has been submitted by the manufacturer for testing, and is monitored on an ongoing basis to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings." The manufacturer also agrees not to change the product after passing the test. "FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation."



- Non-Separating
- Grit Free Paste
- Non-Hardening
- Non-Toxic
- Easy Cleanup
- Indefinite Shelf Life
- Adheres to Oily Threads

## Suitable for use on systems carrying:

Air; Glycerine; Glycol; Steam; Water (hot or cold)

J.C. Whitlam Manufacturing Co.  
P.O. Box 380 • Wadsworth, OH 44282



U.S. & Canada  
Phone: 800-321-8358  
FAX: 800-537-0588  
International  
Phone: 330-334-2524  
FAX: 330-334-3005

[www.joinpipe.com](http://www.joinpipe.com)  
Email: [info@jcwitlam.com](mailto:info@jcwitlam.com)

© 2011 J.C. Whitlam Manufacturing Co.

Distributed By:

 **WHITLAM**  
**PLUMB-PRO**  
The Industry Standard for Over 100 Years  
[PowerSealPlus.com](http://PowerSealPlus.com)