

WHITLAM

SELECT UNYTE

Pipe Thread Compound with PTFE*

SELECT-UNYTE is an all purpose, non-seizing, PTFE thread sealing compound that produces a leak proof seal on all types of metal and plastic threaded connections. SELECT-UNYTE is a smooth, grit free, completely homogenized, white PTFE paste. Temperature Range Use: -50°F (-45°C) to 400°F (+204°C).

FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin*, Zytel*, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon**, Cyclocac***, and all types of metal.

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (435 kPa)

Liquids:

Up to 10,000 PSI (1450 kPa)

U.S. FEDERAL SPECIFICATIONS

Select-Unyte exceeds TT-S-1732

AVAILABLE SIZES

Stock#	Size
TF2	2 oz. tube (.56 kg)
TF4	1/4 pint (118 ml)
TF8	1/2 pint (237 ml)
TF16	1 pint (473 ml)
TF32	1 quart (.95 L)
TF1	1 gal. (3.785 L)
TF5	5 gal. (18.9 L)
TF55	55 gal. (208 L)

*Dupont registered trademarks

**Celanese registered trademark

***General Electric Plastics registered trademark

- Non-Separating
- Grit Free Paste
- Adheres to Oily Threads
- Easy Cleanup
- Safe for PVC & CPVC
- Nontoxic/Non Combustible

Suitable for use on systems carrying:

Acids, Dilute	Corrosives	Hydrogen	Propane
Air, Compressed	Cutting Oils	Inert Gases	Refrigeration
Aliphatic Solvents	Diesel Fuel Oil	Jet Fuel	Gases
Alkalis, Dilute	Fatty Acids	Kerosene	Soap, Liquid
Ammonia	Freons (All)	LP Gases	Steam Lines
Brine	Gasohol	Lacquer	Sugar, Liquid
Butane	Gasoline	Mineral Oils	Vegetable Oils
Carbon Dioxide	Glycol	Naphtha	Water
Castor Oils	Heating Oils	Natural Gas	Xylol
Chlorinated Water	Helium, Gaseous	Nitrogen Gas	
Coal Tar Naphtha	Hydraulic Oils	Petroleum Solvents	



Approved for Natural Gas, Propane, LP Gas and Butane.



NSF Standard 14
NSF Standard 61



Underwriters Laboratories of Canada Listed Pipe Joint Compound Form1 Issue No. 1351

"For a Positive Leak-proof Seal"

Distributed By:



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282

U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005

whitlam-plumbpro.com

© 2006 J.C. Whitlam Manufacturing Co.

WHITLAM
PLUMB-PRO

The Industry Standard for Over 100 Years

*PolyTetraFluoroEthylene