

Go for the Green !

WHITLAM PRO-GREEN

USAGE:

Solvent weld all classes of PVC solvent weld pipe and fittings.

PIPE SIZE:

Pressure Pipe:

Up to 3"

Non-Pressure Pipe:

Up to 6"

PRESSURE RANGE USE:

Liquids:

Up to 300 PSI (2068 kPa)

TEMPERATURE RANGE

Use:

0°F (-17°C) to 120°F (380°C)

CONSISTENCY/COLOR:

Medium Bodied

Green Colored Cement

SET TIME:

20 seconds

COMPLETE CURE TIME:

24 Hours

SPECIFICATIONS:

Meets ASTM D2564

AVAILABLE SIZES:

Stock#	Size
IR4	¼ pint (118 ml)
IR8	½ pint (237 ml)
IR16	1 pint (473 ml)
IR32	1 quart (.95 L)
IR1	1 gal. (3.785 L)

J.C. Whitlam Manufacturing Co.
P.O. Box 380
Wadsworth, OH 44282
U.S. & Canada
Phone: 800-321-8358
FAX: 800-537-0588
International
Phone: 330-334-2524
FAX: 330-334-3005



*Irrigation Glue
Low VOC
Medium Bodied
PVC Cement*

PRO-GREEN One Step Irrigation Cement is a fast set, low VOC*, medium bodied solvent weld cement specifically formulated for the irrigation and sprinkler contractor.

- **One Step Cement**
- **Excellent for "Pulling" Pipe**
- **Low VOC* Formula**
- **No Primer Required****
- **Works Well on Wet or Dry Pipe**
- **Great for Flexible PVC Pipe**
- **Allows for Immediate Pressure Testing**
- **Fast Set**

 **WHITLAM**

The Industry Standard for Over 100 Years



*Maximum VOC emissions as applied and tested per SCAQMD Rule 1168, Test Method 316A: 250 g/l

**Use without primer when acceptable by local code.