

PLUMB-PRO

Utility Straps

Black EPDM Rubber Utility Straps



PLUMB-PRO Professional Quality EPDM (Ethylene Propylene Diene Monomer) Rubber Straps are made in the U.S.A. from the highest quality materials to offer a tie-down utility strap with exceptional strength. The EPDM rubber polymer used in the strap has a high crosslink density that allows them to be used in the harshest of environments without the risk of oxidation or weather stressed cracking. The strap is specifically engineered to absorb stress through a taper where the square head meets the body of the strap. The single piece molded construction ensures exceptional strength and stretch resiliency. The square head also provides a stronger point of contact with the S-Hook, the point where most strap failures occur.

- **High Quality UV Resistant EPDM Rubber**
- **Squared Head and Tapered Neck Reduces Strap Stress**
- **Rubber Polymer has a High Crosslink Density**
- **Fully Assembled with "S" Hooks Attached**
- **Made in the U.S.A**

An assortment of lengths from 9" to 41" are available. The straps come fully assembled with S-Hooks that will not bend or break under normal use.

CAUTION:

Always wear safety glasses during tie down and disconnect. Failure to do so may result in serious injury. Inspect strap and hooks before each use - do not use if damaged. Do not use as a primary tie down device for load. Max safe stretch = 150% Strap Length.

Stock Code	Size	Items per Case
#US9	9" (23 cm)	50
#US9A	9" (23 cm)	12
#US15	15" (38 cm)	50
#US15A	15" (38 cm)	12
#US20	20" (51 cm)	50
#US20A	20" (51 cm)	12
#US31	31" (79 cm)	50
#US31A	31" (79 cm)	12
#US41	41" (104 cm)	50
#US41A	41" (104 cm)	12



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, Ohio 44282
U.S. & Canada
Phone: 800-321-8358
Fax: 800-537-0588
International
Phone: 330-334-2524
Fax: 330-334-3005

Distributed by:



WHITLAM
Specialty Products