

# PIPE SLIME PIPE GASKET LUBE SLIME-SPEC

## PRODUCT DESCRIPTION

### PRODUCT

**PIPE SLIME** Pipe Gasket Lube

### TYPE

**PIPE SLIME** Pipe Gasket Lube is a unique pipe joining lubricant that has been specially formulated to prevent turbidity, taste, and/or odor problems in new water main installations. **PIPE SLIME** offers low temperature application and will not promote bacterial growth.

### RECOMMENDED USES

A green viscous gasket lubricant for lubricating all rubber and plastic gaskets used in mechanical pipe coupling including, C900, C900/RJ™\*, SDR, HDPE, Polyethylene, Polypropylene, PVC and Ductile pipe and fittings. **PIPE SLIME** insures proper alignment of gaskets for correct fit during pipe installation. It works well on wet or dry surfaces and is nontoxic and suitable for use on potable water systems. **PIPE SLIME** is odorless and cleans up easily. Safe for use on all metal, plastic and rubber gasketed pipe. Excellent for jobs that require low temperature application.

### COLOR/CONSISTENCY

Lime Green. A smooth, thixotropic lubricant. Remains a paste at temperatures above 150°F (66°C). Will not break down if repeatedly frozen and thawed.

### TEMPERATURE RANGE USE

0°F (-18°C) to 150°F (66°C)

### CORROSIVENESS

Non-corrosive

### FLAMMABILITY

Nonflammable

### SLIME-SPEC

© 2014 J.C. Whitlam Manufacturing Company  
This product is manufactured in the U.S.A.

[www.pipelube.com](http://www.pipelube.com)

\*C900/RJ™ is a CertainTeed Trademark

## DRYING TIME

Drying time of the lubricant will vary with weather conditions; therefore, it is important to join the pipe and gasket as soon as possible after applying the lubricant. If drying should occur before joining the pipe with the gasket, re-swab the pipe and gasket immediately. For best results, apply with a cotton swab applicator.

## PACKAGING

### U.S. Measure:

| <u>Stock Code</u>                         | <u>Size</u>        |
|---|--------------------|
| <b>Plastic Container w/ Twist Top Lid</b> |                    |
| SLIME4                                    | ¼ pint (118 ml)    |
| <b>Plastic Container w/ Twist Top Lid</b> |                    |
| SLIME32                                   | 1 quart (.95 L)    |
| <b>Pail w/ Handle</b>                     |                    |
| SLIME1                                    | 1 gal. (3.785 L)   |
| SLIME3                                    | 3.5 gal. (13.25 L) |
| SLIME5                                    | 5 gal. (18.9 L)    |
| <b>55 Gallon Drum</b>                     |                    |
| SLIME55                                   | 55 gal. (208 L)    |

### WEIGHT PER U.S. GALLON

8.43 lbs. (3.82 kg) ± 0.2


### SHIPPING WEIGHT PER CASE

| <u>Stock Code</u> | <u>Case Weight</u>  | <u>#/Case</u> |
|-------------------|---------------------|---------------|
| SLIME4            | 8 lbs. (3.6 kg)     | 24            |
| SLIME32           | 28 lbs. (12.7 kg)   | 12            |
| SLIME1            | 37 lbs. (16.8 kg)   | 4             |
| SLIME3            | 32 lbs. (14.5 kg)   | 1             |
| SLIME5            | 45 lbs. (20.4 kg)   | 1             |
| SLIME55           | 500 lbs. (226.8 kg) | 1             |




Meets  
NSF Standard 14 &  
NSF Standard 61

## DIRECTIONS FOR USE



**Step 1: Clean bell of pipe.**  
Remove any loose dirt, gravel, rust, scale, or foreign material. Remove standing water for best results.




**Step 2: Clean spigot of pipe as in Step 1. Surfaces must be thoroughly clean before application of "Pipe Slime".**



**Step 3: Apply "Pipe Slime" liberally to the bell of pipe. For best results use a cotton swab applicator.**



**Step 4: Apply "Pipe Slime" liberally to the spigot of pipe. Keep the lubricated surfaces free from dirt.**



**Step 5: Immediately after application of the lubricant, assemble the joint. Apply even pressure and insert the spigot into the bell.**



P.O. Box 380  
Wadsworth, Ohio 44282  
Phone: 330-334-2524  
Fax: 330-334-3005  
Email: [info@jwhitlam.com](mailto:info@jwhitlam.com)  
Website: [www.joinpipe.com](http://www.joinpipe.com)