

E-Z TURN FAUCET AND VALVE HEAT PROOF GREASE HPG-SPEC

PRODUCT DESCRIPTION

PRODUCT

E-Z TURN Faucet and Valve Heat Proof Grease

TYPE

E-Z TURN Faucet and Valve Heat Proof Grease is a waterproof, nontoxic, high temperature, amber colored, general purpose grease.

Specially formulated for use on all metal faucet and valve stems carrying air, steam and hot or cold water.

Prevents sticking and rust. Assures free movement and extended life.

RECOMMENDED USES

E-Z TURN Faucet and Valve Heat Proof Grease can be used for lubricating valve stems of faucets, valves, ballcocks, plungers, packings, washers or anywhere a water resistant grease is required.

COLOR/CONSISTENCY

Amber Paste

PHYSICAL PROPERTIES

Flash Point, COC: 450° F (232° C)
Melting Temperature: 350° F (176° C)

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
HPG2	2 oz. (56.7 g)

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
HPG2	5 lbs. (2.3 kg)	24

WEIGHT PER U.S. GALLON

7.4 lbs. (3.4 kg) ± 0.2

ENVIRONMENTAL STATEMENT

Can be used on potable water since it is safe and nontoxic.

DIRECTIONS FOR USE

VALVE BODIES:

1. Unscrew valve bonnet nut.
2. Rotate valve stem counter clockwise to remove the valve body.
3. Clean stem and threads if necessary.
4. Apply a liberal amount of **E-Z TURN** to the stem and stem threads.
5. Reassemble in reverse order. Tighten bonnet nut lightly. Retighten if there is seepage when system pressure is restored.

BALLCOCK AND FLOAT LINKAGES:

1. Clean and descale if necessary.
2. Apply liberal amounts of **E-Z TURN** to all rubbing and pivoting surfaces.
3. Apply a thin film of **E-Z TURN** to all metal parts in contact with water to prevent corrosion and scale build up.
4. Apply **E-Z TURN** to float linkage threads to prevent corrosion.

HPG-SPEC

© 2018 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.

 **WHITLAM**
P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com