

# WAX RINGS REGULAR AND FLANGED S1WR, S1WS-SPEC

## PRODUCT DESCRIPTION

### PRODUCT

**WHITLAM WAX RINGS**  
a microcrystalline wax gasket.

### TYPE

**WHITLAM WAX RINGS** are for setting floor outlet toilet bowls. They form a water, gas and odor tight seal. Flanged wax rings are excellent for built up floors.

### RECOMMENDED USES

**WHITLAM WAX RINGS** fit 3" (7.62 cm) and 4" (10.16 cm) waste lines. Fits all standard drains.

### COLOR/CONSISTENCY

Brown/Solid wax

### PHYSICAL/CHEMICAL PROPERTIES

#### **Appearance:**

Solid

#### **Physical state:**

Solid

#### **Substance type:**

Mixture

#### **Odor:**

No odor

#### **Melting point/range:**

154-176° F (68-80°C)

#### **Specific gravity:**

0.78-0.84

#### **Flash point, method used:**

392°F (200°C) Open Cup

#### **Water solubility:**

Negligible

### U.S. FEDERAL SPECIFICATIONS

Meets Specification TT-P-1536A

### ENVIRONMENTAL STATEMENT

Zero VOC content

### **S1WR, S1WS-SPEC**

MADE IN MEXICO

© 2018 J.C. Whitlam Manufacturing Company

## PACKAGING

### **U.S. Measure:**

<b>Stock Code</b>	<b>Size</b>
<b>Boxed</b>	
S1WR	Regular 1" (2.54 cm) x 5.5" (13.97 cm)
S1WS	Flanged 1.75" (4.45 cm) x 5.75" (14.61 cm)

### SHIPPING WEIGHT PER CASE

<b>Stock Code</b>	<b>Case Weight</b>	<b>#/Case</b>
S1WR	23 lbs. (10.4 kg)	48
S1WS	15 lbs. (6.8 kg)	24

## DIRECTIONS FOR USE

1. Set the toilet bowl upside down on a smooth and soft surface. Remove the wrapping from the wax ring and place it around the discharge opening. Press the wax ring softly on the toilet to install.
2. Turn the toilet and place it over the floor ensuring that its discharge opening is perfectly aligned with the drain hole in the floor. Twist it gently to ensure seal.
3. Set screws to secure the toilet on the floor.

 **WHITLAM**  
P.O. Box 380  
Wadsworth, Ohio 44282  
Phone: 330-334-2524  
Fax: 330-334-3005  
Email: info@jcwhitlam.com  
Website: www.joinpipe.com