

TALON URINAL CLEANER AND DESCALER

LIQUID URINAL CLEANER AND DESCALER

TUBC-SPEC

PRODUCT DESCRIPTION

PRODUCT

TALON Urinal Cleaner and Descaler

TYPE

TALON Urinal Cleaner and Descaler

Keeps urinals open and free flowing and eliminates uric odors.

TALON Urinal Cleaner and Descaler is an inhibited drain opener engineered to dissolve urinal drain blockages and restrictions. Formulated with buffered inhibitors to prevent corrosion in cast iron systems. Will not harm copper, steel, PVC or ABS drain pipes.

- Non-Fuming
- Safe for Pipes
- Quickly Opens Drains
- Eliminates Drain Odors
- Cleans Rust and Scale

RECOMMENDED USES

TALON Urinal Cleaner and Descaler

Cleans, disinfects and deodorizes in one step. Acid compatible detergent system removes resistant stains and increases disinfectant action.

Excellent for:

- Urinals
- Toilet Bowls
- General Descaling

Will not etch toilet bowls or urinal surfaces.

COLOR/CONSISTENCY

Clear Blue / Liquid

APPLICATION PRECAUTIONS

**FOR PROFESSIONAL USE:
READ CAUTIONS AND FIRST AID
PROCEDURES BEFORE USE.**

**DO NOT MIX WITH BLEACH OR
AMMONIA.**

**DO NOT APPLY TO CHROME OR
METAL FIXTURES.**

**MUST WEAR PROPER
PROTECTIVE EQUIPMENT.**

**SEE SAFETY DATA SHEET (SDS) FOR
COMPLETE PRECAUTIONS FOR SAFE
HANDLING AND USE.**

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
TUBC32	Quart (.95 L)
TUBC1	Gallon (3.785 L)

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
TUBC32	34 lbs. (15.4 kg)	12
TUBC1	43 lbs. (19.5 kg)	6

WEIGHT PER U.S. GALLON

DIRECTIONS FOR USE

Directions for Urinal Use:

If completely clogged remove standing water otherwise flush urinal or toilet to determine amount of clog.

Remove any debris, urinal screens, and/or odor control blocks.

Shut off automatic flush sensor.

Pour 8 - 16 oz. of **TALON Urinal Cleaner and Descaler** into urinal/toilet bowl and allow product to remain for 13-15 minutes.

Brush interior surfaces with bowl brush.

Turn on automatic flush sensors and flush to rinse.

Repeat the process if urinal is completely clogged or slow to drain.

Directions for Toilet Bowl Use:

Flush toilet before cleaning.

Apply 4-6 oz. **TALON Urinal Cleaner and Descaler** under and around rim to coat the inside of bowl.

Scrub entire bowl and allow to sit for 10 minutes for disinfecting.

Do not allow pets or children to access the toilet during this time.

Flush toilet.

TUBC-SPEC

© 2020 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.