

# TALON URINAL CLEANER AND DESCALER

## LIQUID URINAL CLEANER AND DESCALER

### TUBC-SPEC

#### PRODUCT DESCRIPTION

##### PRODUCT

TALON Urinal Cleaner and Descaler

##### TYPE

TALON Urinal Cleaner and Descaler

Keeps urinals open and free flowing and eliminates uric odors.

TALON Urinal Cleaner and Descaler is an inhibited drain opener engineered to dissolve urinal drain blockages and restrictions. Formulated with buffered inhibitors to prevent corrosion in cast iron systems. Will not harm copper, steel, PVC or ABS drain pipes.

- Non-Fuming
- Safe for Pipes
- Quickly Opens Drains
- Eliminates Drain Odors
- Cleans Rust and Scale

##### RECOMMENDED USES

TALON Urinal Cleaner and Descaler

Cleans, disinfects and deodorizes in one step. Acid compatible detergent system removes resistant stains and increases disinfectant action.

Excellent for:

- Urinals
- Toilet Bowels
- General Descaling

Will not etch toilet bowls or urinal surfaces.

##### COLOR/CONSISTENCY

Clear Blue / Liquid

#### APPLICATION PRECAUTIONS

**FOR PROFESSIONAL USE:  
READ CAUTIONS AND FIRST AID  
PROCEDURES BEFORE USE.**

**DO NOT MIX WITH BLEACH OR  
AMMONIA.**

**DO NOT APPLY TO CHROME OR  
METAL FIXTURES.**

**MUST WEAR PROPER  
PROTECTIVE EQUIPMENT.**

**SEE SAFETY DATA SHEET (SDS) FOR  
COMPLETE PRECAUTIONS FOR SAFE  
HANDLING AND USE.**

#### PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
TUBC32	Quart (.95 L)
TUBC1	Gallon (3.785 L)

#### SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
TUBC32	34 lbs. (15.4 kg)	12
TUBC1	43 lbs. (19.5 kg)	4

#### WEIGHT PER U.S. GALLON

#### DIRECTIONS FOR USE

Directions for Urinal Use:

If completely clogged remove standing water otherwise flush urinal or toilet to determine amount of clog.

Remove any debris, urinal screens, and/or odor control blocks.

Shut off automatic flush sensor.

Pour 8 - 16 oz. of **TALON Urinal Cleaner and Descaler** into urinal/toilet bowl and allow product to remain for 13-15 minutes.

Brush interior surfaces with bowl brush.

Turn on automatic flush sensors and flush to rinse.

Repeat the process if urinal is completely clogged or slow to drain.

Directions for Toilet Bowl Use:

Flush toilet before cleaning.

Apply 4-6 oz. **TALON Urinal Cleaner and Descaler** under and around rim to coat the inside of bowl.

Scrub entire bowl and allow to sit for 10 minutes for disinfecting.

Do not allow pets or children to access the toilet during this time.

Flush toilet.

#### **TUBC-SPEC**

© 2022 J.C. Whitlam Manufacturing Company  
This product is manufactured in the U.S.A.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.  
Phone: 1-330-334-2524 • FAX 1-330-334-3005  
Email: [info@jcwhitlam.com](mailto:info@jcwhitlam.com)  
Website: [www.jcwhitlam.com](http://www.jcwhitlam.com)