BIG BUBBLE GAS LEAK DETECTOR LD-SPEC

PRODUCT DESCRIPTION

PRODUCT

BIG BUBBLE Gas Leak Detector, Dauber Formula

TYPE

BIG BUBBLE is a noncorrosive, nonfreezing, nontoxic, non-soap base, **fluorescent yellow** leak detector.

Will not cause corrosion or deterioration of metal, copper, brass or plastic.

RECOMMENDED USES

BIG BUBBLE Gas Leak Detector is for use on all types of connections on gas lines, air lines, gas cylinders, refrigeration condensers, evaporators, air pumps, and tanks used for storing gases or any system carrying gaseous products.

BIG BUBBLE'S water soluble polymer detects large and small leaks by forming bubbles which remain for up to 10 minutes.

Not recommended for oxygen systems.

TEMPERATURE RANGE USE

-7°F (-21°C) to 212°F (100°C)

COLOR/CONSISTENCY

Fluorescent Yellow Liquid

U.S FEDERAL SPECIFICATIONS

Meets Federal Specification MIL-L-25567-C.

ASTM SPECIFICATIONS

Meets ASTM G188-05

PACKAGING

U.S. Measure:

Stock Code Size
Yorker Bottle
LD1OZ 1 oz. (29.6 ml)
Dauber Top Container
LD8 ½ pint (237 ml)
Plastic Jug w/ Spout

LD1 Gallon (3.785 L) **55 Gallon Drum**

LD55 55 Gallon (208 L)

WEIGHT PER U.S. GALLON

8.41 lbs. (3.8 kg) ±0.2

SHIPPING WEIGHT PER CASE

| Stock | | |
|-------------|---------------------|--------|
| <u>Code</u> | Case Weight | #/Case |
| LD10Z | 4 lbs. (1.8 kg) | 36 |
| LD8 | 16 lbs. (7.3 kg) | 24 |
| LD1 | 55 lbs. (24.9 kg) | 6 |
| LD55 | 502 lbs. (227.7 kg) | 1 |
| | | |

DIRECTIONS FOR USE

- 1. Apply liberal amounts of **BIG BUBBLE** Gas Leak Detector by swabbing the area where the leak is suspected.
- 2. The slightest pressure leak will cause bubbles to form and remain for up to 10 minutes.

KEEP OUT OF REACH OF CHILDREN.

SEE SAFETY DATA SHEET (SDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

MADE IN THE U.S.A.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A. Phone: 1-330-334-2524 • FAX 1-330-334-3005 Email: info@jcwhitlam.com Website: www.gasleakdetector.info