GREENS COAT TURF COLORANT GC-SPEC

PRODUCT DESCRIPTION

PRODUCT

GREENS COAT Turf Colorant

RECOMMENDED USES

Our exclusive proprietary formula was designed and developed for a fast and economical way to restore the natural, healthy, lush green color to dormant or distressed turf on golf courses, football fields, soccer pitches, baseball fields, field hockey and similar sports areas as well as home lawns and commercial landscapes. **GREENS COAT** is used to color and improve the appearance of dormant, semi-dormant or discolored turf. It is a permanent green pigment which will not harm turf grass and can be applied at any time during the year.

COLOR/SHEEN

Evergreen

DRYING TIME

Fast, 30 - 60 minutes at $77^{\circ}F$ ($25^{\circ}C$) and 50% relative humidity.

VISCOSITY

68-72 K.U. Stormer Viscometer

ENVIRONMENTAL STATEMENT

GREENS COAT is environmentally friendly, contains no hazardous chemicals, heavy metals or other inert ingredients harmful to turf.

APPLICATION DATA

SURFACE PREPARATION

Non-dormant grass should be cut to desired level (approx. 1" to 1 $\frac{1}{2}$ ") prior to the initial application. Apply when ground is dry.

APPLICATION METHODS

Shake or agitate container thoroughly before use. When applying by spray, thin with water to a consistency suitable for spray equipment selected for applications. Do not mix more product than will be used in a day. For best results, apply at a low to medium pressure. Avoid overspray on concrete, blacktop, cart paths or any other objects where color is not desired. Do not apply if rain threatens. If temperate weather is forecasted after application, cover the area with a water resistant tarp to prevent color from being "washed-out".

APPLICATION EQUIPMENT

Conventional Spray:

Non-specialized spray equipment in a wide range of sizes and types can be used.

RECOMMENDED COVERAGE RATES

GREENS COAT has been formulated to last throughout the dormant period or until grass starts to grow again. However, for golf courses and sports fields it is recommended that 2-3 lighter applications be made. The area covered will vary depending upon the type of equipment selected, condition of turf being treated and the turf color desired. Apply at a rate of 8 – 16 oz. per acre with a minimum 50 gallons of water. Some experimentation and adjustments may be required to obtain the desired color.

CLEANUP

For best results, use soap and warm water immediately after use on all spray equipment, tanks, nozzles and screens.

PACKAGING

U.S. Measure:

Stock Code Size
Plastic Jug w/ Spout

GC32 1 quart (.95 L) GC1 1 gallon (3.785 L)

Plastic Pail w/ Handle

GC5 5 gallon (18.9 L)

WEIGHT PER U.S GALLON

 8.49 ± 0.2 lbs.

SHIPPING WEIGHT PER CASE

Stock		
<u>Code</u>	Case Weight	#/Case
GC32	34 lbs. (15.4 kg)	12
GC1	66 lbs. (29.9 kg)	6
GC5	53 lbs. (24.0 kg)	1



Division of J.C. Whitlam Manufacturing Co.
P.O. Box 380
Wadsworth, Oh 44282
Phone: 330-334-2524
Fax: 330-334-3005
www.whitlampaint.com
www.greenscoat.com

© 2022 Whitlam Paint Company This product is manufactured in the U.S.A.