

SLUDGE•B•GONE

FUEL OIL ADDITIVE

SBG-SPEC

PRODUCT DESCRIPTION

PRODUCT

SLUDGE•B•GONE Fuel Oil Additive

DESCRIPTION

A premium, all season fuel oil treatment.

RECOMMENDED USES

SLUDGE•B•GONE is an excellent chemical treatment for cleaning burner orifices in oil burners; dissolving sludge and dissipating water in No. 2 fuel oil.

- PREVENTS CORROSION IN NO. 2 FUEL TANKS
- DISSOLVES SLUDGE
- REMOVES WATER
- IMPROVES OIL FLOW
- PREVENTS FUEL LINE FREEZE-UP
- REDUCES SOOT
- STABILIZES SUMMER STORAGE

SLUDGE•B•GONE reduces fuel costs by dissolving sludge and rust in No. 2 fuel oil tanks. Contains a special water dispersant to eliminate and prevent troublesome sludge by imparting a uniform consistency to fuel oils. Prevents ice freeze-ups by eliminating condensate water.

If used regularly, SLUDGE•B•GONE helps prevent clogging of strainers and nozzles. Clears fuel lines and prevents leaks by fighting corrosion. Reduces soot by increasing burner efficiency.

COLOR/CONSISTENCY

Clear Liquid

WEIGHT PER U.S. GALLON

8.2 lbs. (3.7 kg) ± 0.2

TEMPERATURE RANGE USE

0°F (-32°C) to 140°F (61°C)

SBG-SPEC

© 2020 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

APPLICATION PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY. CONTAINS PETROLEUM DISTILLATES. MAY BE HARMFUL OR FATAL IF SWALLOWED. AVOID CONTACT WITH HANDS, FACE, AND EYES.

USE ONLY IN WELL VENTILATED AREA. KEEP AWAY FROM HEAT AND OPEN FLAME. COMBUSTIBLE MIXTURE.

FOR PROFESSIONAL USE ONLY.

SEE SAFETY DATA SHEET (SDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

ENVIRONMENTAL STATEMENT

SLUDGE•B•GONE prevents the formation of sludge to increase fuel oil burner efficiency and decrease fuel consumption.

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Plastic Jug w/ Spout	
SBG32	Quart (.95 L)
Metal Can w/ Handle	
SBG1	Gallon (3.785 L)

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
SBG32	26 lbs. (11.8 kg)	12
SBG1	35 lbs. (15.9 kg)	4

DIRECTIONS FOR USE

1. Add one quart (.95 L) for each 250 gallons (946 L) of fuel oil.
2. For continued treatment, use one quart (.95 L) for each 1000 gallons (3785 L) consumed.

**FOR BEST RESULTS
ADD JUST PRIOR TO OIL DELIVERY**

FOR REMOVING WATER CONDENSATE:

1. Two quarts of SLUDGE•B•GONE Fuel Oil Additive in a 550 gallon (2080 L) tank will remove condensation and help prevent ice formation in outside storage.
2. Treat fuel oil by adding SLUDGE•B•GONE at the beginning of each heating season.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.
Phone: 1-330-334-2524 • FAX 1-330-334-3005
Email: info@jcwhitlam.com
Website: www.sludgebgone.com