

STAINLESS STEEL PTFE TAPE GRAY PIPE JOINT COMPOUND TAPE SST-TAPE-SPEC

PRODUCT DESCRIPTION

PRODUCT

STAINLESS STEEL PTFE[†] TAPE

Gray Pipe Joint Compound Tape

DESCRIPTION

STAINLESS STEEL PTFE TAPE is a gray, all purpose, non-seizing, 4 MIL PTFE (polytetrafluoroethylene) thread sealing compound in tape form that produces a leakproof seal on all types of stainless steel threaded fittings, works exceptionally well on assemblies with sharp coarse threads.

RECOMMENDED USES

STAINLESS STEEL PTFE TAPE can be used on all types of stainless steel threaded fittings for passage of water potable and non-potable, most chemicals, oxygen, gas, hydraulic and high pressure lines.

Chemically inert. It is suitable for use on systems carrying almost all types of chemicals and gases including:

Acids, Dilute	Hydraulic Oils
Air, Compressed	Hydrogen
Aliphatic Solvents	Inert Gases
Alkalis, Dilute	Jet Fuel
Ammonia	Kerosene
Brine	Lacquer
Butane	L P Gases
Carbon Dioxide	Mineral Oils
Castor Oils	Naphtha
Chlorinated Water	Natural Gas
Coal Tar Naphtha	Nitrogen Gas
Cutting Oils	Propane
Diesel Fuel Oil	Refrigeration Gases
Fatty Acids	
Freons (All)	Soap, Liquid
Gasohol	Steam Lines
Gasoline [^]	Sugar, Liquid
Glycol	Vegetable Oils
Heating Oils	Water
Helium, Gaseous	Xylol

COLOR/CONSISTENCY

The tape is gray in color. It shall be free of visible voids, cracks, folds, contamination and has consistent physical properties. **STAINLESS STEEL PTFE TAPE** has an indefinite shelf life.

SST-TAPE-SPEC

© 2020 J.C. Whitlam Manufacturing Company

TEMPERATURE RANGE USE

Gases:

-450°F (-268°C) to 500°F (260°C)

Liquids:

-450°F (-268°C) to 500°F (260°C)

PRESSURE RANGE USE

Gases:

up to 10,000 PSI (1450 kPa)

Liquids:

up to 3,000 PSI (435 kPa)

The system may be pressurized immediately after assembly.

FOR USE ON THREADED

ABS, PVC, CPVC, Delrin*, Zytel*, FlowGuard GOLD** CPVC, Blazemaster** CPVC, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon***, Cyclocac**** plastics, and all types of metal.

CORROSIVENESS

STAINLESS STEEL PTFE TAPE is non-corrosive, and prevents the corrosion and seizing of threads.

U.S. FEDERAL SPECIFICATIONS

STAINLESS STEEL PTFE TAPE

meets MIL-T-27730A.

Meets ANSI LC 7-2009 for Pipe Joint Sealing Compounds and Materials.

ENVIRONMENTAL STATEMENT

STAINLESS STEEL PTFE TAPE is chemically inert to virtually all environments. Non Flammable.

DENSITY

1.2 g/cm nominal

TENSILE STRENGTH LONGITUDINAL

Up to 10,000 PSI

ELONGATION

100% Nominal

THICKNESS

0.0040" to 0.0045"

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Plastic Spool	
SST260	½" x 260" (1.27 cm x 6.6 m)
SSTW260	¾" x 260" (1.9 cm x 6.6 m)

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
SST260	1 lbs. (0.5 kg)	12
SSTW260	1 lbs. (0.5 kg)	12

DIRECTIONS FOR USE

1. Remove plastic spool.
2. Apply tape clockwise onto male threads.
3. Make up joint in a normal manner.

On large diameter pipe 4" (10.2 cm) and up, first wrap the pipe threads with two or more thicknesses of **STAINLESS STEEL PTFE TAPE**, then apply **BLUE-MAGIC** over the tape.



The Industry Standard for Over 100 Years

P.O. Box 380 • Wadsworth, OH 44282 U.S.A.
Phone: 1-330-334-2524 • FAX 1-330-334-3005
Email: info@icwhitlam.com
Website: www.joinpipe.com

[†]PolyTetraFluoroEthylene [^]Contact J.C. Whitlam Mfg. Co. for compatible blends.

*Dupont registered trademarks **FlowGuard GOLD and Blazemaster are registered trademarks of The Lubrizol Corporation

Celanese registered trademark *General Electric Plastics registered trademark

PTFE (polytetrafluoroethylene) is the same chemical composition as Dupont Teflon®

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.