

Eliminate Turbidity from the Start!

BLUE LUBE PIPE GASKET LUBE

USES:

A blue viscous gasket lubricant for lubricating all rubber and plastic gaskets used in mechanical pipe coupling including Gruvlok* and Victaulic** type fittings. Blue Lube insures proper alignment of gaskets for correct fit during pipe installation. It works well on wet or dry surfaces and is suitable for use on potable water systems. Blue Lube is odorless and cleans up easily. Safe for use on all metal, plastic, and concrete pipe.

CONSISTENCY/COLOR:

Smooth, thixotropic
Lubricant/Blue

SPECIFICATIONS:

Meets NSF Standard 14
and NSF Standard 61

TEMPERATURE RANGE USE:

0°F (-17°C) to 150°F (66°C)

AVAILABLE SIZES

Stock#	Size
GLP4	1/4 Pint (118 ml)
GLP16	Pint (473 ml)
GLP32	Quart (.95 L)
GLP1	Gallon (3.785 L)
GLP5	5 Gallon (18.9 L)
GLP55	55 Gallon (208 L)



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358
FAX: 800-537-0588

International

Phone: 330-334-2524
FAX: 330-334-3005

www.blue.lube.info

© 2020 J.C. Whitlam Manufacturing Co.

Blue Lube is an emulsified polymer based lubricant that is specially formulated to prevent turbidity, taste, and/or odor problems in new water main installations. Independent tests performed by major municipalities have shown **Blue Lube** will not promote turbidity, or transfer taste and odor, and completely flushes out of the system. **Blue Lube** will not promote bacterial growth and is safe to use on all metal, plastic, and concrete pipe.



- Nontoxic
- Tasteless & Odorless
- Water Soluble
- Flushes Completely from the System
- Does Not Promote Bacterial Growth



Clean and Clear

Blue Lube is clean, clear, tasteless and odorless. A sure, safe alternative to oleate based lubricants.



NSF Standard 14
NSF Standard 61

Distributed By:



Typical Paste



BLUE LUBE Paste



WHITLAM

The Industry Standard for Over 100 Years