

# BLACK FLASH FLASHING CEMENT COMPOUND BF-SPEC

## PRODUCT DESCRIPTION

### PRODUCT

**BLACK FLASH Flashing Cement Compound**

### TYPE

**BLACK FLASH Flashing Cement Compound** is an all-weather compound made of only the highest quality, tough plastic asphalt oils with long-fiber. Non-hardening; stays pliable in any weather. Can be applied to damp surfaces; never pulls away from the joint. Won't crack at any temperature.

### RECOMMENDED USES

**BLACK FLASH Flashing Cement Compound** is used for sealing around flashings, skylights, downspouts, gutters, chimneys, soil pipe, concrete pipe, and concrete vaults. Excellent for repairing leaks in roofs, gutters and old flashings. **BLACK FLASH** has excellent adhesion. Adheres to metal, plastic, concrete, tile and all types of roof shingles. Works great as a mastic for sealing soil-pipe and as a lead substitute in lead/oakum joints. Provides a waterproof and airtight barrier immediately on application. Long-lasting performance. Consistent formula that is non-separating and ready to use. Maintains an indefinite shelf life if properly sealed and does not contain any objectionable odors.

### COLOR/CONSISTENCY

Black / Heavy paste

## APPLICATION PRECAUTIONS

**WARNING:  
COMBUSTIBLE**

**DO NOT USE NEAR HEAT,  
SPARKS OR OPEN FLAME.**

**KEEP OUT OF REACH OF CHILDREN.**

**SEE SAFETY DATA SHEET (SDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.**

### PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
<b>Cartridge</b>	
BFC	1/10 gal. (.37 ml)
<b>Can</b>	
BF32	Quart (.95 L)
<b>Can w/ Handle</b>	
BF1	Gallon (3.785 L)
<b>Pail w/ Handle</b>	
BF5	5 Gallon (18.9 L)

### SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
BFC	11 lbs. (5.0 kg)	12
BF32	33 lbs. (15.0 kg)	12
BF1	40 lbs. (18.1 kg)	4
BF5	47 lbs. (21.3 kg)	1

### WEIGHT PER U.S. GALLON

9.16 lbs. (4.2 kg) ±0.2

## DIRECTIONS FOR USE

Apply with putty knife or trowel and work well into holes, cracks and crevices so that all entrapped air is eliminated.

Tools can be easily cleaned with common petroleum solvents.

### DRYING TIME

Set time: 1 hour to touch.  
Complete cure time is 12 hours.

### U.S. FEDERAL SPECIFICATION

Meets SS-C-153

### TEMPERATURE APPLICATION USE

30°F (-1°C) to 120°F (48°C)

### TEMPERATURE RANGE USE

-70°F (-56°C) to 140°F (60°C)

### **BF-SPEC**

© 2020 J.C. Whitlam Manufacturing Company  
This product is manufactured in the U.S.A.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.  
Phone: 1-330-334-2524 • FAX 1-330-334-3005  
Email: [info@jcwhitlam.com](mailto:info@jcwhitlam.com)  
Website: [www.joinpipe.com](http://www.joinpipe.com)