

WHITLAM POWER SEAL



Thread Sealing Compound

POWER SEAL PLUS is specially formulated for the fire protection industry for use on all metal threaded connections, **FlowGuard Gold®**, **BlazeMaster®**, and **Corzan®** pipe and fittings.



SYSTEM COMPATIBLE

- **Non-Separating**
- **Grit Free Paste**
- **Non-Hardening**
- **Non-Toxic**
- **Easy Cleanup**
- **Indefinite Shelf Life**
- **Adheres to Oily Threads**

Suitable for use on systems carrying:

Air; Glycerine; Glycol; Steam; Water (hot or cold)

TEMPERATURE RANGE USE:

Gases:

-15°F (-26°C) to 400°F (204°C)

Liquids:

-15°F (-26°C) to 400°F (204°C)

Brushable to -15°F (-26°C)

PRESSURE RANGE USE:

Gases:

Up to 5,000 PSI (351.5 kg/cm²)

Liquids:

Up to 10,000 PSI (703.1 kg/cm²)

U.S. FEDERAL SPECIFICATIONS:

Power Seal exceeds TT-S-1732

AVAILABLE SIZES:

Stock#	Size
Brush Top Can	
POW16B	1 pint (473 ml)
POW32B	1 quart (.95 L)
Flat Top Can	
POW16	1 pint (473 ml)
POW32	1 quart (.95 L)
POW1	1 gal. (3.785 L)
Pail	
POW5	5 gal. (18.9 L)
Drum	
POW55	55 gal. (208 L)

FBC™ System Compatible indicates that this product has been tested and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan® and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358
FAX: 800-537-0588

International

Phone: 330-334-2524
FAX: 330-334-3005



www.jcwhitlam.com
Email: info@jcwhitlam.com

© 2020 J.C. Whitlam Manufacturing Co.

Distributed By:

 **WHITLAM**
PowerSealPlus.com