

Joining Pipe Since 1900



# WHITLAM

## FIRE SPRINKLER PRODUCTS

MADE IN U.S.A.

### Thread Sealing Compound



**FBC**  
SYSTEM COMPATIBLE

- Grit Free Paste
- Non-Hardening
- Easy Cleanup
- Indefinite Shelf Life
- Adheres to Oily Threads

POWER SEAL PLUS Thread Sealing Compound sets another standard in thread sealing technology. POWER SEAL PLUS is manufactured with the finest grade PTFE to provide the smoothest, nondrying, grit free thread sealant available.

### POWER SEAL PLUS

AVAILABLE SIZES:

Stock#	Size
Brush Top Can	
POW32B	1 quart (.95 L)
Plastic Container with Twist Top Lid	
POW32	1 quart (.95 L)
Pail with Handle	
POW5	5 gal. (18.9 L)
55 Gallon Steel Drum	
POW55	55 gal. (208 L)

### Anaerobic PTFE Sealant



- Solvent Free
- LOW VOC (<0.1%)
- Instant Sealing > 200 PSIG
- Resistant to Corrosives
- Easy Disassembly

TALON ANAEROBIC PTFE THREAD SEALANT seals threaded joints on metal piping including Stainless Steel and Aluminum. Excellent for NPT pipe connections. Assists assembly by lubricating contact surfaces. After curing, the seal surpasses the burst pressure rating of the pipe and resists most industrial chemicals and gases. Excellent for prefab work.



AVAILABLE SIZES:

Stock#	Size
Squeeze Tube	
TLA250	250 ml (8.5 oz.)
Brush Top Container	
TLA350	350 ml (11.8 oz.)
Plastic Container with Twist Top Lid	
TLA750	750 ml (25.4 oz.)
Pail with Handle	
TLA14	14 L (3.7 gal.)

### Pipe Joint Lubricant



**FBC**  
SYSTEM COMPATIBLE

**NSF Certified**

AVAILABLE SIZES:

Stock#	Size
Plastic Container with Twist Top Lid	
QS32	1 quart (.95 L)
Pail with Handle	
QS1	1 gal. (3.785 L)
QS5	5 gal. (18.9 L)
55 Gallon Steel Drum	
QS55	55 gal. (208 L)

- Non-Toxic/Biodegradable
- Excellent Lubricity
- Water Soluble
- Will Not Support Bacteria
- Non-Drying Formula

**WHITLAM**  
The Industry Standard for Over 100 Years  
[www.joinpipe.com](http://www.joinpipe.com)

J.C. Whitlam Mfg. Co.  
P.O. Box 380  
Wadsworth, OH 44282  
U.S. & Canada  
Phone: 800-321-8358  
FAX: 800-537-0588  
International  
Phone: +1-330-334-2524  
FAX: +1-330-334-3005