



TALON™ NICKEL

ANTI-SEIZE LUBRICANT AND THREAD COMPOUND

TALON NICKEL ANTI-SEIZE Lubricant and Thread Sealant is a lead free, non-seizing, nickel based, lubricant and thread sealant. A premium quality lubricant that may be used to prevent seizing, corrosion and galling where extreme temperature conditions exist. Contains a high percentage of micro-fine nickel flakes in a semi-synthetic grease carrier and is fortified with high quality rust and corrosion inhibitors. Excellent for use on high pressure corrosive systems.

FOR USE ON:

Applications where copper, lead, molybdisulfide, chlorides and fluorides cannot be tolerated. Excellent for stainless threads, blowers, bolts, catalytic crackers, couplings, drill collars, flanges, fuel nozzles, gaskets, gas burners, gear reducers, manhole studs, nuts, pipe fittings, plugs, pumps, screws, tool joints, turbine studs, and valves. Recommended where copper contamination must be avoided, under conditions of extreme pressure and temperature, and with stainless steel, titanium and nickel alloys.

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (211 kg/cm²)

Liquids:

Up to 10,000 PSI (703 kg/cm²)

TEMPERATURE RANGE USE:

0°F (-17°C) to 2600°F (1427° C)

U.S. MILITARY SPECIFICATIONS

TALON Nickel exceeds MIL-A-907E

AVAILABLE SIZES (Net Weight)

Stock#	Size
NI8	8 oz. (.227 kg)
NI16	1 lb. (.454 kg)

- **Lead Free**
- **Prevents Seizing**
- **Corrosion Resistant**
- **Adheres to Oily Threads**
- **Temperature Range: 0°F to 2600°F**



Semi-synthetic, grease carrier and fortified with high quality rust and corrosion inhibitors.

Non-Seizing and Non-Galling. Excellent for Stainless Steel.

Nickel Flake reduces friction between the thread of the pipe and thread of the fitting.

High Temperature 2600°F Extreme Service

TALON NICKEL ANTI-SEIZE Lubricant and Thread Sealant

Suitable for use on systems carrying:

Air	Anhydrous Ammonia	Inert Gases	Steam Lines
Acetylene	Brine	Natural Gas	Sugar, Liquid
Alkalis, Dilute	Carbon Dioxide	Nitrogen Gas	Vinyl Monomers
Anhydrous Sodium Hydroxide (50%)	Chlorinated Water	Refrigeration Gases	Water
	Freons (All)	Soap, Liquid	

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358
FAX: 800-537-0588

International

Phone: 330-334-2524
FAX: 330-334-3005



Distributed By:



The Industry Standard for Over 100 Years

"Freedom from Leaks"