

WHITLAM



TALON DRAIN OPENER

RECOMMENDED USES:

Drains
Grease Traps
Septic Systems
Root Control

USAGE:

Talon Drain Opener is a dry, flake drain opener for clearing grease, hair and other organic matter from drains. Also can be used to control root growth.

COLOR/CONSISTANCY:

White Flake

APPLICATION PRECAUTIONS:

Talon Drain Opener is for professional use only. Read entire product information and instructions on reverse side before using.

AVAILABLE SIZES:

Stock #	Size	Items/ Case
TDC1	1 lb. (454 g)	24
TDC2	2 lbs. (907 g)	12



- Works in Less than 60 Sec.*
- Destroys Hair and Grease Instantly
- Will not Harm Chrome, Polished Brass or Plastic
- Safe for Septic Systems
- Non-Acid Opener

Talon Drain Opener is specifically formulated for use by Professional Plumbing Maintenance Personnel working in hotels, restaurants, apartment and condominium complexes, nursing homes and schools. Talon Drain Opener opens drains clogged by grease, hair and other organic matter, controls root growth, and opens grease traps fast without the dangers associated with acid type drain openers. Talon Drain Opener can be used monthly as preventive maintenance to keep drains clear and flowing smoothly.

STOCK CODE	SIZE	CONTAINER	ITEMS/CASE	CASE WEIGHT
TDC1	1 lb. - 454 g	Plastic Container**	24	33 lbs. - 15.0 kg
TDC2	2 lb. - 907 g	Plastic Container**	12	16 lbs. - 7.3 kg

* Use warm or hot tap water for a faster reaction time

** Childproof Caps

See reverse side for complete handling and safety information.

For Professional Use Only - Not For Retail Sale
ONLY FOR USE BY PLUMBING PROFESSIONALS AND TRAINED MAINTENANCE PERSONNEL.

Distributed By:



The Industry Standard for Over 100 Years

www.jcwhitlam.com

J.C. Whitlam Manufacturing Co.

P.O. Box 380
Wadsworth, Ohio 44282

U.S. & Canada

Phone: 800-321-8358

Fax: 800-537-0588

International

Phone: 330-334-2524

Fax: 330-334-3005



TALON DRAIN OPENER

DIRECTIONS FOR USE **READ DIRECTIONS BEFORE USING**

DRAINS: Run hot water to warm lines. Add 1 cup TALON DRAIN OPENER slowly and directly into drain opening. Run just enough hot tap water to dissolve all the TALON DRAIN OPENER. Do not use boiling water with this product. Let stand for one minute, flush with more hot tap water. To prevent drains from clogging in the future, add ½ to 1 cup of TALON DRAIN OPENER once a month. If drain is totally clogged, open drain with a snake to allow at least slight flow, then add TALON DRAIN OPENER as directed above.

GREASE TRAPS: Use 2 pounds of TALON DRAIN OPENER for every 100 gallon capacity of the grease trap to keep grease traps working properly. Pour in TALON DRAIN OPENER slowly, then add hot tap water until it is completely dissolved. Let sit overnight for best results.

TOILET BOWLS AND CHINA FIXTURES:

Follow directions under "DRAINS", but premix each ½ cup TALON DRAIN OPENER with 2 cups of cold water before adding to drain. Add TALON DRAIN OPENER slowly to the 2 cups of water and stir constantly to avoid a violent exothermic reaction.

SEPTIC SYSTEMS: Use 6 pounds of TALON DRAIN OPENER to treat a 500 gallon capacity septic tank. Pour TALON DRAIN OPENER along with very hot water down sink or tub drain, run hot water for a minute after all TALON DRAIN OPENER is down the drain. Add 6 pounds of TALON DRAIN OPENER once per year to help prevent the build up of grease and solid waste in system.

ROOT CONTROL: Add 2 pounds slowly to any drain leading to a root clogged drain. Let water run in drain until TALON DRAIN OPENER reaches roots. Let sit overnight then flush with hot tap water. Use monthly to control roots.

APPLICATION PRECAUTIONS

- **READ ENTIRE PRODUCT LABEL AND SAFETY DATA SHEET BEFORE USING PRODUCT.**
- **TALON DRAIN OPENER CONTAINS SODIUM HYDROXIDE.**
- **HIGHLY CORROSIVE. CAN CAUSE SEVERE BURNS AND/OR BLINDNESS.**
- **HARMFUL OR FATAL IF SWALLOWED.**
- **DO NOT MIX WITH ACIDS, BLEACH, ALKALINE OR OTHER CHEMICALS.**
- **KEEP AWAY FROM CHILDREN.**
- **ALWAYS WEAR RUBBER GLOVES AND GOGGLES OR FACE SHIELD WHEN HANDLING TALON DRAIN OPENER.**
- **DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.**
- **DO NOT USE IN DISPOSALS OR MIX IN AN ALUMINUM CONTAINER.**
- **DO NOT USE IF ACIDS OR OTHER CHEMICALS ARE IN THE SYSTEM.**
- **KEEP CONTAINER CLOSED AND TIGHTLY CAPPED WHEN NOT IN USE.**
- **AFTER HANDLING TALON DRAIN OPENER, WASH THOROUGHLY, INCLUDING CONTAMINATED EQUIPMENT, SHOES AND CLOTHING.**
- **NEUTRALIZE IRRITATED SKIN WITH VINEGAR.**
- **WHEN USING, PROVIDE SUFFICIENT VENTILATION TO PREVENT BUILDUP OF VAPORS OR MIST.**
- **STORE IN A COOL DRY AREA OUT OF REACH OF CHILDREN.**
- **DO NOT DROP.**
- **AVOID SPILLS. THIS PRODUCT WILL ATTACK ALL ORGANIC MATERIAL.**
- **USE ORIGINAL CONTAINER ONLY. DO NOT TRANSFER.**
- **FOR SALE, USE, AND STORAGE BY PROFESSIONALS ONLY ! NOT FOR CONSUMER USE.**



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, Ohio 44282

U.S. & Canada	International
Phone: 800-321-8358	Phone: 330-334-2524
Fax: 800-537-0588	Fax: 330-334-3005