

Select the Best!

Select...



Pipe Thread Compound with PTFE<sup>△</sup>

SELECT-UNYTE is an all purpose, non-seizing, PTFE thread sealing compound that produces a leak proof seal on all types of metal and plastic threaded connections. SELECT-UNYTE is a smooth, grit free, completely homogenized, white PTFE paste. Temperature Range Use: -50°F (-45°C) to 400°F (204°C).

- **Non-Separating**
- **Grit Free Paste**
- **Adheres to Oily Threads**
- **Easy Cleanup**
- **Safe for PVC & CPVC**
- **Nontoxic/Non Combustible**

FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin\*, Zytel\*, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon\*\*, Cyclocac\*\*\*, and all types of metal.

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (210.9 kg/cm<sup>2</sup>)

Liquids:

Up to 10,000 PSI (703.0 kg/cm<sup>2</sup>)

U.S. FEDERAL SPECIFICATIONS

Select-Unyte exceeds TT-S-1732

AVAILABLE SIZES

Stock#	Size
TF2	2 oz. tube (56 g)
TF4	1/4 pint (118 ml)
TF8	1/2 pint (237 ml)
TF16	1 pint (473 ml)
TF32	1 quart (.95 L)
TF1	1 gal. (3.785 L)
TF5	5 gal. (18.9 L)
TF55	55 gal. (208 L)

\*Dupont registered trademark

\*\*Celanese registered trademark

\*\*\*General Electric Plastics registered trademark

Suitable for use on systems carrying:

Acids, Dilute	Cutting Oils	Hydraulic Oils	Nitrogen (Gaseous)
Air, Compressed	Diesel Exhaust Fluid (DEF)	Hydrogen	Petroleum Solvents
Aliphatic Solvents	Diesel Fuel Oil	Inert Gases	Propane
Alkalis, Dilute	Fatty Acids	Jet Fuel (JP4,JP5, & JP6)	Refrigeration Gases
Ammonia	Freons (All)	Kerosene	Soap, Liquid
Brine	Gasohol	LP Gases	Steam Lines
Butane	Gasoline <sup>†</sup>	Lacquer	Sugar, Liquid
Carbon Dioxide	Glycol	Mineral Oils	Vegetable Oils
Castor Oils	Heating Oils	Naphtha	Water (Potable)
Chlorinated Water	Helium (Gaseous)	Natural Gas	Xylol



Approved for Natural Gas, Propane, LP Gas and Butane.



NSF Standard 14  
NSF Standard 61

pw-G/dww/sw



Underwriters' Laboratories of Canada Listed for Natural Gas, Gasoline, Petroleum Oils, Propane & Butane



"For a Positive Leak-proof Seal"

Distributed By:



The Industry Standard for Over 100 Years

J.C. Whitlam Manufacturing Co.  
P.O. Box 380 • Wadsworth, OH 44282  
U.S. & Canada

Phone: 800-321-8358  
FAX: 800-537-0588

International

Phone: 330-334-2524  
FAX: 330-334-3005

www.select-unyte.com

