



TALON™



PTFE PIPE THREAD COMPOUND

FOR USE ON THREADED:

PVC, CPVC, Delrin*, Zytel*,
Fiberglass, Nylon, Polypropylene,
Polybutylene, Polyethylene,
Celcon**, Cyclocac***, and all types
of metals including: Stainless
Steel, Iron, Copper, Galvanized,
Brass, and Aluminum.

PRESSURE RANGE USE:

Gases:

Up to 5,000 PSI (351.5 kg/cm²)

Liquids:

Up to 10,000 PSI (703.1 kg/cm²)

TEMPERATURE RANGE USE:

10°F (-12°C) TO 500°F (260°C)

U.S. FEDERAL SPECIFICATIONS

TALON exceeds TT-S-1732

AVAILABLE SIZES

Stock#	Size
TAL4	1/4 pint (118 ml)
TAL8	1/2 pint (237 ml)
TAL8A†	1/2 pint (237 ml)
TAL16	1 pint (473 ml)
TAL32	1 quart (.95 L)
TAL1	1 gal. (3.785 L)
TAL5	5 gal. (18.9 L)
TAL55	55 gal. (208 L)

*Dupont registered trademark

**Celanese registered trademark

***General Electric Plastics registered
trademark

† TAL8A is packaged in a display box

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005

www.joinpipe.com



© 2018 J.C. Whitlam Manufacturing Co.


TALON PTFE Pipe Thread Compound is a triple lubricating, all-purpose, non-seizing, VOC free, industrial grade thread sealing compound that provides "Freedom from Leaks™" on all types of metal and plastic threaded connections. TALON PTFE Pipe Thread Compound contains Graphite, Ceramic Microspheres, and Virgin PTFE for optimal sealing.

- Zero VOC
- Triple Lubricating
- Adheres to Oily Threads
- Safe for PVC & CPVC
- Nontoxic/Noncombustible



2x the amount of PTFE
than typical thread
paste reduces the need for
PTFE Tape.

Graphite
reduces friction
between the
thread of the
pipe and thread
of the fitting.



Ceramic Microspheres
act like mini ball
bearings that lubricate
then compress to form
a positive seal.



Suitable for use on systems carrying:

Acids, Dilute	Cutting Oils	Helium (Gaseous)	Natural Gas
Air, Compressed	Diesel Exhaust	Hydraulic Oils	Nitrogen (Gaseous)
Aliphatic Solvents	Fluid (DEF)	Hydrogen	Petroleum Solvents
Alkalis, Dilute	Diesel Fuel Oil	Inert Gases	Propane
Ammonia	Fatty Acids	Jet Fuel	Refrigeration Gases
Brine	Food Processing	(JP4, JP5, & JP6)	Soap, Liquid
Butane	Freons (All)	Kerosene	Steam Lines
Carbon Dioxide	Gasohol	LP Gases	Sugar, Liquid
Castor Oils	Gasoline ^A	Lacquer	Vegetable Oils
Chlorinated Water	Glycol	Mineral Oils	Water (Potable)
Coal Tar Naphtha	Heating Oils	Naphtha	Xylol



Approved for
Natural Gas,
Propane, LP Gas
and Butane.



pw-G/dww/sw
NSF Standard 14
NSF Standard 61

"Freedom from Leaks™"

Distributed By:

W **WHITLAM**
The Industry Standard for Over 100 Years

PTFE is PolyTetraFluoroEthylene ^AContact J.C. Whitlam Mfg. Company for compatible blends.