

# WHITLAM

## SEALANT FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin\*, Zytel\*,  
FlowGuard GOLD\*\* CPVC,  
Blazemaster\*\* CPVC, Fiberglass,  
Nylon, Polypropylene, Polybutylene,  
Polyethylene, Celcon\*\*\*, Cynolac\*\*\*\*,  
and all types of metal.

Works excellent as a chlorine tab  
adhesive in new water main  
installations. Readily dissolves along  
with the chlorine tab as the tab  
becomes active through water  
contact. Will not transfer taste, odor  
or particulate.

## PRESSURE RANGE USE

### Gases:

Up to 3,000 PSI (211 kg/cm<sup>2</sup>)

### Liquids:

Up to 6,000 PSI (422 kg/cm<sup>2</sup>)

## U.S. FEDERAL SPECIFICATIONS

T-U TYPE 555 exceeds TT-S-1732

Meets International Fuel Gas Code  
403.9.3 for Thread Joint Compounds.

## AVAILABLE SIZES

Stock#	Size
TU4	1/4 pint (118 ml)
TU8	1/2 pint (237 ml)
TU16	1 pint (473 ml)
TU32	1 quart (.95 L)
TU1	1 gal. (3.785 L)
TU5	5 gal. (18.9 L)
TU55	55 gal. (208 L)

\*Dupont registered trademarks

\*\* FlowGuard Gold and Blazemaster are  
Lubrizol registered trademarks

\*\*\*Celanese registered trademark

\*\*\*\*General Electric Plastics registered  
trademark

J.C. Whitlam Manufacturing Co.  
P.O. Box 380 • Wadsworth, OH 44282  
U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005

[www.joinpipe.com](http://www.joinpipe.com)



© 2023 J.C. Whitlam Manufacturing Co.

# T-U TYPE 555

## Thread Sealing Compound

**T-U TYPE 555** is a yellow soft-set, odor free, all purpose, non-seizing, thread sealing compound that produces a leak proof seal on all types of metal and plastic threaded connections. **T-U TYPE 555** is completely homogenized and free of any valve destroying grit. Temperature Range Use: -50°F (-45°C) to 400°F (+204°C).

- **Non-Separating**
- **Grit Free Paste**
- **Adheres to Oily Threads**
- **Easy Cleanup**
- **Safe for PVC & CPVC**
- **Nontoxic/Non-Combustible**

## Suitable for use on systems carrying:

Acids, Dilute  
Air, Compressed  
Aliphatic Solvents  
Alkalis, Dilute  
Ammonia  
Brine  
Butane  
Carbon Dioxide  
Castor Oils  
Chlorinated Water  
Coal Tar Naphtha

Cutting Oils  
Diesel Fuel Oil  
Freons (All)  
Gasoline\*  
Glycol  
Heating Oils  
Helium, Gaseous  
Hydraulic Oils  
Hydrogen  
Inert Gases  
Jet Fuel

Kerosene  
LP Gases  
Lacquer  
Mineral Oils  
Natural Gas  
Nitrogen Gas  
Petroleum Solvents  
Propane  
Refrigeration  
Gases

Soap, Liquid  
Steam Lines  
Sugar, Liquid  
Vegetable Oils  
Water



Approved for Natural  
Gas, Propane, LP Gas  
and Butane.



NSF Standard 14  
NSF Standard 61  
pw-G/dww/sw



“For a Positive Leak-proof Seal”

**Distributed By:**

**W WHITLAM**  
The Industry Standard for Over 100 Years

\*Contact J.C. Whitlam Mfg. Company for compatible blends.