

TALON URINAL TRAP SEALANT

WATERLESS URINAL TRAP SEALANT

TUTS-SPEC

PRODUCT DESCRIPTION

PRODUCT

TALON Waterless Urinal Trap Sealant

TYPE

TALON Waterless Urinal Trap Sealant Eliminates urinal odor problems.

TALON Waterless Urinal Trap Sealant will not evaporate which helps eliminate drain odors long term. Has a fresh citrus scent. Higher viscosity than most trap primers will help prevent it from being washed out.

RECOMMENDED USES

TALON Waterless Urinal Trap Sealant ready to use trap liquid sealant is ideal for use in waterless urinals. Its fluid has a specific gravity lower than urine which allows it to float creating a long lasting liquid seal. As the urinal is used, small amounts of the sealant will be drained into the waste line and will need to be replenished (usually after 1,500 uses). It is biodegradable.

TALON Waterless Urinal Trap Sealant remains indefinitely in the trap with no use, sealing trap odors.

COLOR/CONSISTENCY

Purple / Liquid

FREEZE POINT PROTECTION

-20°F (28.9°C)

PACKAGING

U.S. Measure:

| <u>Stock Code</u> | <u>Size</u> |
|----------------------|---------------|
| Plastic Jug w/ Spout | |
| TUTS32 | Quart (.95 L) |

SHIPPING WEIGHT PER CASE

| <u>Stock Code</u> | <u>Case Weight</u> | <u>#/Case</u> |
|-------------------|--------------------|---------------|
| TUTS32 | 27 lbs. (12.2 kg) | 12 |

WEIGHT PER U.S. GALLON

7.16 lbs. (3.25 kg) ± 0.2

DIRECTIONS FOR USE

For general maintenance pour 3 ounces **TALON Waterless Urinal Trap Sealant** directly into the waste opening toward the back of the urinal.

Service frequency based on the uses per work day:

1-75 users: service monthly
76-150 users: service twice a month
151-225 users: service three times a month
226-300 users: service weekly

SEE SAFETY DATA SHEET (SDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

TUTS-SPEC

© 2023 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.



P.O. Box 380 • Wadsworth, OH 44282 U.S.A.
Phone: 1-330-334-2524 • FAX 1-330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com