

# WHITLAM BLACK SEAL

## RECOMMENDED USES:

**BLACK SEAL** Acrylic Concrete Sealer and Damp-Proof Coating is a single component waterborne coating ideal for seamless waterproofing applications above or below-grade. A quick drying damp-proof coating with high solids that is ideal for most all concrete structures. **BLACK SEAL** offers one coat coverage with full resistance to water. Excellent for interior and exterior use to create a damp-proof coating. Suitable as a top coat on properly primed metals.

Excellent for sealing the following:

- Concrete Pipe and Vaults
- Concrete Block
- Masonry Surfaces
- Precast Concrete Pit Blocks
- Concrete Manholes
- Basement Walls
- Poured Concrete
- Asphalt Surfaces
- Stucco
- Wood

Excellent for wastewater immersion and wastewater wet wells, pump stations, manholes, and excellent for acid/corrosion protection with a pH range of 3-10. Suppresses denitrification and sulphate reduction processes which are responsible for the production of corrosive active metabolites (NO<sub>2</sub>, NH<sub>3</sub>, H<sub>2</sub>S).

## APPLICATION:

The coating can be applied as is by brush, roller, or spray. No thinning is required.

## AVAILABLE SIZES:

Stock#	Size
BSB5	5 gal. (18.9 L) Pail
BSB5	55 gal. (208 L) Drum

J.C. Whitlam Manufacturing Co.  
P.O. Box 380 • Wadsworth, OH 44282  
U.S. & Canada

Phone: 800-321-8358  
FAX: 800-537-0588

## International

Phone: 330-334-2524  
FAX: 330-334-3005

5/2023  
BSB-Flyer

## ACRYLIC CONCRETE SEALER AND DAMP-PROOF COATING



- Fast Dry
- One-Coat Coverage
- Protects Against Water Intrusion
- Suitable Above or Below Grade
- Excellent Adhesion and Durability



A quick drying, acrylic based sealer with satin finish. Provides excellent sealing properties for all types of masonry surfaces including concrete pipe. Offers one-coat coverage with full resistance to water, acids, alkalis, electrolysis and natural elements. Acrylic polymer formulation is used to damp-proof and waterproof below-grade concrete surfaces. Provides permanent waterproof protection. Creates an anti-corrosive, anti-microbial layer.



Distributed By:

**W** WHITLAM  
The Industry Standard for Over 100 Years