

WHITLAM

LOW VOC CPVC CEMENT

USAGE:

Solvent weld CPVC Flow-Guard Gold® pipe and fittings

PIPE SIZE:

Through 2" (5.08 cm) diameter Sch. 80 CPVC pipe, C.T.S. (copper tube size) and potable water pressure pipe.

PRESSURE RANGE USE:

Liquids:

Up to 275 PSI (39.87 kPa)

TEMPERATURE RANGE

Use:

40°F (5°C) to 100°F (38°C)

CONSISTENCY/COLOR:

Medium Bodied
Yellow Colored Cement

PARTIAL SET TIME:

Approx 45 seconds

COMPLETE CURE TIME:

24 Hours

SPECIFICATIONS:

Meets ASTM D2846,
ASTM F493 and
ASTM F3328-18

AVAILABLE SIZES:

Stock#	Size
CPL4	¼ pint (118 ml)
CPL8	½ pint (237 ml)
CPL16	1 pint (473 ml)
CPL32	1 quart (.95 L)

J.C. Whitlam Manufacturing Co.
P.O. Box 380
Wadsworth, OH 44282
U.S. & Canada
Phone: 800-321-8358
FAX: 800-537-0588
International
Phone: 330-334-2524
FAX: 330-334-3005

YELLOW MEDIUM BODIED CEMENT APPROVED FOR

FLOWGUARD GOLD® **PIPE & FITTINGS**



WHITLAM LOW VOC CPVC YELLOW MEDIUM BODIED CEMENT is a smooth consistency, medium bodied cement formulated for use on small and medium solvent weld CPVC pipe and fittings in both cold and hot water applications.

- **One Step Cement**
- **For use on FlowGuard Gold® pipe and fittings**
- **Low VOC* Formula**
- **No Primer Required****

*Maximum VOC emissions as applied and tested per SCAQMD Rule 1168, Test Method 316A: 250 g/l
**Use without primer when acceptable by local code.

Distributed By:

 **WHITLAM**
PLUMB-PRO
The Industry Standard for Over 100 Years
whitlam-plumbpro.com