WHITLAM

FLASHING CEMENT COMPOUND



Indefinite Shelf Life

MADE IN U.S.A.

- **Wet or Dry Application**
- **Pliable in All Weather Conditions**
- **Excellent for Emergency Repairs**
- **Superior Long Term Performance**



Stock Code	Size/Package	Number Per Case
BFC	1/10 gal. (37 L) Cartridge	12
BF32	Quart (.95 L) Can	12
BF1	Gallon (3.785 L) Can w/ Handle	4
	Carr W/ Flaridic	

BLACK FLASH Flashing Cement Compound is a heavy mastic that is used for sealing around flashings, downspouts, gutters, chimneys, soil pipe, concrete pipe, and concrete vaults. Excellent for repairing leaks in roofs, gutters and old flashings. BLACK FLASH has excellent adhesion. Adheres to metal, plastic, concrete, glass, and wood.

BLACK FLASH Flashing Cement

Compound is a professional grade fibered asphalt cement that is nonhardening and stays pliable in any weather condition. Provides a waterproof and airtight barrier immediately on application. Won't crack at any temperature and can be applied to wet or dry surfaces. Always best to remove standing water, but BLACK FLASH will adhere to clean asphalt surfaces that are underwater. A superior compound that offers long-lasting performance. Meets ASTM D4586.

RECOMMENDED USES:

Excellent for sealing the following:

- Chimneys and Flashings
- Corrugated Roofs
- Clay Roof Tiles
- Gaps in Flat Tarred Roofs
- Roof Shingles All Types
- Solar Panel Installations
- Gutters and Downspouts
- Skylights and Roof Vents
- Concrete Pipe
- Concrete Vaults
- Concrete Manhole Cones
- Storage Containers
- Iron Soil Pipe

Excellent for wastewater immersion and wastewater wet wells, pump stations, manholes, and excellent for acid/corrosion protection with a pH range of 3-10.

J.C. Whitlam Manufacturing Co. P.O. Box 380 • Wadsworth, OH 44282

U.S. & Canada

Phone: 800-321-8358 FAX: 800-537-0588 International

Phone: +1-330-334-2524 FAX: +1-330-334-3005

Distributed By:



www.blackflashcement.com

