WHITLAM



Thread Sealing Compound

T-U TYPE 555 is a yellow soft-set, odor free, all purpose, non-seizing, thread sealing compound that produces a leak proof seal on all types of metal and plastic threaded connections. T-U TYPE 555 is completely homogenized and free of any valve destroying grit. Temperature Range Use: -50°F (-45°C) to 400°F (+204°C).

- **Non-Separating**
- **Grit Free Paste**
- **Adheres to Oily Threads**
- **Easy Cleanup**
- Safe for PVC & CPVC
- **Nontoxic/Non-Combustible**

PRESSURE RANGE USE

SEALANT FOR USE ON

and all types of metal.

ABS, PVC, CPVC, Delrin*, Zytel*, FlowGuard GOLD** CPVC, Blazemaster** CPVC, Fiberglass,

Works excellent as a chlorine tab

installations. Readily dissolves along

adhesive in new water main

with the chlorine tab as the tab

becomes active through water contact. Will not transfer taste, odor

Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon***, Cycolac****

THREADED:

Gases:

Up to 3,000 PSI (211 kg/cm²)

Liquids:

or particulate.

Up to 6,000 PSI (422 kg/cm²)

U.S. FEDERAL SPECIFICATIONS

T-U TYPE 555 exceeds TT-S-1732

Meets International Fuel Gas Code 403.9.3 for Thread Joint Compounds.

AVAILABLE SIZES

Stock# Size TU4 1/4 pint (118 ml) 1/2 pint (237 ml) TU8 **TU16** 1 pint (473 ml) 1 quart (.95 L) **TU32** 55 gal. (208 L) **TU55**

*Dupont registered trademarks

- ** FlowGuard Gold and Blazemaster are Lubrizol registered trademarks
- ***Celanese registered trademark
- ****General Electric Plastics registered trademark

Suitable for use on systems carrying:

Acids. Dilute Air, Compressed Aliphatic Solvents Alkalis, Dilute Ammonia Brine Butane Carbon Dioxide Castor Oils **Chlorinated Water** Coal Tar Naphtha

Cutting Oils Diesel Fuel Oil Freons (All) Gasoline* Glycol Heating Oils Helium, Gaseous Hvdraulic Oils Hydrogen Inert Gases Jet Fuel

Kerosene LP Gases Lacquer Mineral Oils **Natural Gas** Nitrogen Gas Petroleum Solvents Propane Refrigeration Gases

Soap, Liquid Steam Lines Sugar, Liquid Vegetable Oils Water



Approved for Natural Gas, Propane, LP Gas and Butane.



NSF Standard 14 NSF Standard 61 pw-G/dwv/sw

THREAD SEALING COMPOUND ROSCA SELLADO COMPUESTO

The Industry Standard for Over 100 Years

"For a Positive Leak-proof Seal"

Distributed By:



Phone: 800-321-8358 FAX: 800-537-0588 International Phone: 330-334-2524 FAX: 330-334-3005

U.S. & Canada

www.joinpipe.com

J.C. Whitlam Manufacturing Co.

P.O. Box 380 • Wadsworth, OH 44282